



1934224-1 Product Details



1934224-1

TE Internal Number: 1934224-1

Active

Z-PACK TinMan Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Board-to-Board Configuration = Co-Planar, Co-Planar/Right Angle, Right Angle
- Connector Assembly
- Connector Style = Receptacle
- Contact Type = Socket
- 120 Positions

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Mating Products \(2\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information	
Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.	Additional Information: <ul style="list-style-type: none"> • Product Line Information Related Products: <ul style="list-style-type: none"> • Tooling • Mating Products (2)

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Connector Type = Connector Assembly • PCB Mounting Orientation = Right Angle • PCB Mount Retention = With • PCB Mount Retention Type = Action/Compliant Tail • PCB Mount Alignment = Without • Sealed = No <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Data Rate (Gb/s) = 10 • Differential Impedance (Ω) = 100 • Contact - Rated Current (A) = 0.5 • Hot Pluggable = No • Operating Voltage Reference = AC • Operating Voltage (VAC) = 250 • UL Voltage Rating (VAC) = 250 <p>Termination Features:</p> <ul style="list-style-type: none"> • Termination Method to PC Board = Through Hole - Press Fit <p>Dimensions:</p> <ul style="list-style-type: none"> • Tail Length (mm [in]) = 2.2 [0.087] • PCB Thickness, Recommended (mm [in]) = 1.57 [0.062] <p>Body Features:</p> <ul style="list-style-type: none"> • Row-to-Row Spacing (mm [in]) = 1.40 [0.055] • Mating Retention = Without <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Type = Socket • Contact Design = Dual Beam • Contact Base Material = Phosphor Bronze • Contact Plating, Mating Area, Material = Gold • Contact Plating, Mating Area, Thickness (μm [μin]) = 0.76 [29.92] • Contact Plating, Termination Area, Material = Matte Tin • Contact Plating, Termination Area, Thickness (μm [μin]) = 0.5 [20] <p>Housing Features:</p> <ul style="list-style-type: none"> • Connector Style = Receptacle • Housing Color = Black • Centerline (mm [in]) = 1.90 [0.075] • Mating Alignment = With • Mating Alignment Type = Guide Slot 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Number of Positions = 120 • Number of Signal Positions = 80 • Number of Rows = 12 • Number of Columns = 10 • Number of Pairs per Connector = 40 • Pairs per Column = 4 • Stackable = No • Differential Signaling = Yes <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant • Agency/Standard = UL • UL Rating = Recognized • UL File Number = E28476 • UL Flammability Rating = UL 94V-0 <p>Environmental:</p> <ul style="list-style-type: none"> • Operating Temperature ($^{\circ}\text{C}$ [$^{\circ}\text{F}$]) = -65 - +90 [-85 - +194] <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Board-to-Board Configuration = Co-Planar, Co-Planar/Right Angle, Right Angle <p>Operation/Application:</p> <ul style="list-style-type: none"> • Contact Transmits (Typical Application) = Signal (Data) <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Tube <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity
---	--

- Housing Material = Liquid Crystal Polymer (LCP)

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

