

CRIMP RINGS & SPADES





✓ Active



TE CONNECTIVITY (TE) PIDG RECT.

PIDG | PIDG

130476

TE Internal Number: 130476

Alias ID: D41039-000, SIML-0-0130476-0

Always EU RoHS/ELV Compliant

Terminal Shape Rectangular Tongue

Stud Diameter 4.34 mm [.17 in]

Tongue Thickness .78 mm [.031 in]

Sealed **No**

Heavy Duty No

Product Drawings

TERMINAL, RECTANGULAR TONGUE, P.I.D.G. WIRE SIZE: 16-14 AWG PDF (TIFF AVAILABLE)

English

TERMINAL, RECTANGULAR TONGUE, P.I.D.G. WIRE SIZE: 16-14 AWG PDF (TIFF AVAILABLE)

English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	8, M4
	Shape Code	RING-055
	Wire/Cable Composition	Stranded
Configuration Features	Terminal Angle	Straight
	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	300

		_
Body Features	Plating Material	Tin
	Plating Thickness (µm)	2.54
	Insulation Sleeve Material	Copper
	Insulation Sleeve Color	Blue
	Insulation Material	Nylon
	Inspection Slot	No
	Insulation Support Sleeve Material	Copper
Contact Features	Terminal Shape	Rectangular Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	4.34 mm [.17 in]
	Tongue Thickness	.78 mm [.031 in]
	Wire Insulation Diameter (Max)	3.8 mm [.149 in]
	Wire Insulation Diameter	2.7 – 3.8 mm [.106 – .15 in]
	Wire Size (AWG)	16 – 14
	Wire Size (mm²)	1.04 – 2.62
	Wire Size (CMA)	2050 – 5180
	Material Thickness	.78 mm [.031 in]
	Overall Length	20.65 mm [.813 in]
Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Blue
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

