

MSD INC.

ENGINEERING DATA SHEET

RELAY TYPE: FCA-210-CX91

COMPUTER PART No.: 9227519

TEST PROCEDURE

MSDP-791

CUSTOMER/SPECIFICATION: CATALOG ITEM

REV N/A

TEST REQUIREMENTS

COIL CURRENT: .04 A OPERATE TIME: 15ms MAX RELEASE TIME: 50ms MAX

CONTACT MAKE BOUNCE: 1ms MAX N.O. BREAK BOUNCE: N/A

CONTACT STABILIZATION TIME: N/A RATED COIL VOLTAGE: 115VAC -50/400 HZ

CONTACT RES.: MFG TEST: 8 Milliohms @ 10 mA FINAL TEST: 10 Milliohms @ 10 mA

CONTACT VOLTAGE DROP: FINAL TEST: 100 mV @ 10 A - 6 Vdc



HI-POT: 1250 Vrms ALL POINTS, EXCEPT 1000 Vrms COIL TO CASE

INSULATION RESISTANCE: 100 MEGOHMS MIN @ 500 Vdc

VIBRATION: N/A

SEAL TEST: 1×10^{-8} MAX LEAK RATE COIL TRANSIENT SUPPRESSION: N/A

OTHER: SEE SPECIAL INSTRUCTIONS BELOW



Prepared By: Date		Approved By: Date	
LES WYNNE 3-15-96			
Rev	ECN No.	Date	
A	96-065	3-15-96	

SPECIAL INSTRUCTIONS

FINAL TEST ONLY: THERE SHALL BE NO ARMATURE NOISE AT
 70.0-60 HZ PULL-IN AND AT
 25.0V-60 HZ HOLD VOLTAGE