



1. BERYLLIUM COPPER 190 HM 0.10 THICK
2. FINISH: NICKEL UNDERPLATE 1.0/3.0 MICRONS
3. PRE-LOAD FORCE: 0.50 N @ CONTACT POINT
4. FORCE @ MAXIMUM DEFLECTION: 0.73 N @ CONTACT POINT
5. MAXIMUM BEAM DEFLECTION: 0.80mm @ CONTACT POINT
6. CRITICAL DIMENSIONS ARE RINGED.
7. DIMENSIONS MARKED (SPC) ARE SUBJECT TO SPC CONTROL.
8. 6800 PCS ONE REEL WITH 100 LEADER EMPTY POCKETS AND 100 TRAILER EMPTY POCKETS. REEL OUTER DIMETER IS \varnothing 330mm, REEL HUB DIMETER IS \varnothing 100mm.
9. RECOMMENDED PCB PAD SIZE: 2.75 X 0.90 mm.

CUSTOMER DRAWING

DO NOT SCALE		PDM:		A3/B
Drawn	LL	8-May-06	 ITT Industries Cannon Electronics (SZ) Co. Ltd. Toupandun Industrial Area, Jinda Cheng, Xiner Village, Shajing Town, Baoan District, Shenzhen City PRC 518125	Pro/E Generic Model
Checked	KT	8-May-06		Title
Engineer	LL	8-May-06		MICRO UNIVERSAL CONTACT 1.8 mm
C	RIE-1688, ADD PCB PAD SIZE INTO NOTES	8-May-06	Ref: Scale 10.000 Sheet 1 of 1	Drwg. No. CU-120220-0202 iss/rev C
B	RIE-1438 RELEASED	25-May-05		
A	ADD DIMS	02-Jan-05		
-	RELEASED	20-Sep-04		
Iss Rev	DCN/ECN or Description	Date	This is issued in strict confidence on condition that it is not used as a basis for manufacture or sale and that it is not copied reprinted or disclosed to a third party either wholly or in part without the prior written consent of ITT Industries © 30-Mar-05	