

## Housing - HC-B 24-TFL-76/M1PG29G - 1771914


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing, for single locking latch, height 76 mm, with screw connection, 1x Pg29, straight cable entry



### Key commercial data

|                                      |  |
|--------------------------------------|--|
| Packing unit                         | 1 pc   |
| GTIN                                 | <br>4 017918 036591 |
| Weight per Piece (excluding packing) | 419.7 GRM  |
| Custom tariff number                 | 85389099   |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                         |                 |
|-------------------------|-----------------|
| Height                  | 76 mm           |
| Width                   | 43 mm           |
| Length                  | 120 mm          |
| Wrench size, union nut  | 37 mm           |
| External cable diameter | 18 mm ... 27 mm |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|              |  |
|--------------|--|
| Note         | For contact inserts HC-B24, BB46, BBB64, D64, DD108, M |
| Type         | B24  |
| Housing type | Sleeve housing   |

# Housing - HC-B 24-TFL-76/M1PG29G - 1771914

## Technical data

### General

|                              |                          |
|------------------------------|--------------------------|
| Locking type                 | for single locking latch |
| No. of cable outlets         | 1                        |
| Cable exit                   | Straight                 |
| Screw connection             | with                     |
| Type of the screw connection | 1x Pg29                  |
| Housing material             | Aluminum die-cast        |
| Housing surface material     | Powder-coated, gray      |
| Cable gland material         | Nickel-plated brass      |
| Cable seal material          | NBR                      |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Approvals

### Approvals

---

# Housing - HC-B 24-TFL-76/M1PG29G - 1771914

## Approvals

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

## Approval details



## Drawings

Dimensioned drawing

