



#### General ordering data

Order No.	1886590000
Part designation	WSI 4/LD 10-36V AC/DC
Version	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
EAN	4032248492077
Qty.	50 pc(s).

#### Product notes

Function	10 - 36
----------	---------

#### Additional technical data

Colour of insulating material	black
Connection direction	on side
End plate required	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screw connection
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Fuse terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	12 A
Min. cross-section (CSA)	AWG 22
Max. cross-section (CSA)	AWG 12

**Conductors for clamping (rated connection)**

Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>
Type of connection	Screw connection
Connection direction	on side
No. of connections	2
Stripping length	8 mm
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Tightening torque range	0.5...0.8 Nm
Torque level with DMS electric screwdriver	2
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	4 mm <sup>2</sup>
Stranded, min.	0.5 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	4 mm <sup>2</sup>
AWG conductor size, min.	AWG 22
AWG conductor size, max.	AWG 12

**Dimensions**

Width	9.1 mm
Height of lowest version	54 mm
Length	50.7 mm

**Disconnect terminals**

Torque level with DMS electric screwdriver	2
--	---

**Display element**

Operating voltage for display, max.	36 V
Operating voltage for display, min.	10 V
Type of voltage for indicator	AC/DC

**Fuse terminals**

Cartridge fuse	G-Si. 1 x 1/4
Display	LED
Fuse holder (cartridge holder)	Screwable
Operating voltage, max.	36 V
Type of voltage for indicator	AC/DC

**Rating data**

Rated cross-section	4 mm <sup>2</sup>
Rated voltage	500 V
Rated current	12 A
Standards	IEC 60947-7-3

**UL rating data**

Voltage (UL)	300 V
Current (UL)	12 A

**UL rating data**

Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

**Approvals**

Approvals institutes


**Classifications**

ETIM 2.0	EC000899
ETIM 3.0	EC000899
eClass 4.1	27-14-11-16
eClass 5.0	27-14-11-16
eClass 5.1	27-14-11-16

**Similar products**

Order No.	Part designation	Version
1886580000	WSI 4	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1880430000	WSI 4/2	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1880410000	WSI 4/2/LD 10-36V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1880390000	WSI 4/2/LD 140-250V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1880440000	WSI 4/2/LD 30-70V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1880420000	WSI 4/2/LD 60-150V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1886550000	WSI 4/LD 140-250V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1886560000	WSI 4/LD 30-70V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1886570000	WSI 4/LD 60-150V AC/DC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1011000000	WSI 6	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1011060000	WSI 6 OR	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, Orange, TS 35
1011010000	WSI 6 SW	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, black, TS 35
1028200000	WSI 6 TR	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, transparent, TS 35
1014000000	WSI 6/2 GZ/DEF63	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1014300000	WSI 6/2/LD 60-150VDC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1014400000	WSI 6/2/LD 250AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1014100000	WSI 6/2/LD 10-36V DC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1014200000	WSI 6/2/LD 30-70V DC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1012300000	WSI 6/LD 60-150V DC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1012400000	WSI 6/LD 250AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1011300000	WSI 6/LD 10-36V DC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35
1012200000	WSI 6/LD 30-70V DC/AC	Fuse terminal, 6 mm <sup>2</sup> , Screw connection, Wemid, dark beige, TS 35