

# Customer Specification PART NO. 1176L

#### Construction

				Diameters (In	Diameters (In)	
1) Component 1		6 X 1 COND	6 X 1 COND			
a) Conductor		22 (7/30) AWG	22 (7/30) AWG TC			
b) Insulation		0.010" Wall, No (LSZH)	0.010" Wall, Nom. Low Smoke Zero Halogen (LSZH)		0.049	
(1) Color Code		Alpha Wire Con	Alpha Wire Company Color Code D			
Cond	Color	Cond	Color	Cond	Color	
1	BLACK	3	WHITE	5	ORANGE	
2	RED	4	GREEN	6	BLUE	
2) Cable Assembly		6 Components	6 Components Cabled			
a) Twists:		5.3 Twists/foot	5.3 Twists/foot (min)			
3) Jacket		0.030" Wall, No (LSZH)	0.030" Wall, Nom.,Low Smoke Zero Halogen (LSZH)		0.209 (0.221 Max.)	
a) Color(s)		SLATE	SLATE			
b) Print		EXXXXXX 75C C(UL) TYPE CM * = Factory Cod	ALPHA WIRE-* P/N 1176L 6C 22 AWG EXXXXXX 75C (UL) TYPE CM OR 75C C(UL) TYPE CMG LSZH CE ROHS * = Factory Code [Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]			

### **Applicable Specifications**

1) UL	СМ	75°C
2) CSA International	FT4	
	C(UL) TYPE CMG	75°C
3) CE:	LVD 73/23/EEC Amendment 93/68/EEC	

#### Environmental

1) EU Directive 2002/95/EC(RoHS):			
	All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.		
2) REACH Regulation (EC 1907/2006):			
	This product does not contain any of the 16 substances listed on the European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.		

## Properties

Physical & Mechanical Properties		
1) Temperature Range	-20 to 75°C	
2) Bend Radius	10X Cable Diameter	
3) Pull Tension	33 Lbs, Maximum	
Electrical Properties	(For Engineering purposes only)	
1) Voltage Rating	300 V <sub>RMS</sub>	
2) Inductance	0.17 μH/ft, Nominal	
3) Conductor DCR	16.4 O/1000ft @20°C, Nominal	

#### Other

1) Packaging		
a) Bulk(Made-to-order)		
2) Notes:		
a) Flammability - Passes IEC 60332-1		
b) Acid Gas Generation - Passes IEC 60754-1 and 60754-2		
c) Smoke Emission - Passes IEC 61034-2		

Elizabeth, NJ 07207

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors ice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and spont with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



### **RoHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number:1176L

1176L, RoHS-Compliant Commencing With3/1/2009Production

This document certifies that the Alpha part numbers cited above are manufactured in accordance with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003, better known as the RoHS Directives, with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The reader is referred to these Directives for the specific definitions and extents of these Directives. **No Exemptions are required for RoHS Compliance on this item**.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.1% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB) Polybrominated Diphenyl Ethers (PBDE)	0.1% by weight (1000 ppm)
Including Deca-BDE	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire Company:

Dave Watson, Director of Engineering &QA

11/8/2010