

TOLERANCE OF LEAD LENGTH:

UP TO 24 INCHES $[609.6] = \pm .12 [\pm 3.0]$ 24 INCHES $[609.6] \& UP = \pm 1\%$

- 2. MARKED PER MIL-STD-130.
- 3. TO MATE WITH AMP LGH-1
 - RECEPTACLE WITH .88 [22.4] BARREL DEPTH.
- 4. OPERATING VOLTAGE: 20 KVDC AT 0 TO 70,000 FEET, -55°C TO 125°C.
- 5. MIN LEAD LENGTH IS 5 INCHES.

THIS DRAWING IS A CONTROLLED DOCUMENT.			C.C.THOMAS	9-13-91 9-23-91		ETE TE Connectivity				
DIMENSIONS:	orriginate of confict.		S.GLADFELTER	9-23-91	NAME					
INCHES[MM]			S.GLADFELTER		LEAD ASS'Y, LGH-1,					
	0 PLC 1 PLC 2 PLC	± - ± - ± .02 [0.5]	PRODUCT SPEC			DOUBLE MOLDED END				
	3 PLC 4 PLC ANGLES	±	APPLICATION SPEC —		SIZE		DRAWING NO		RESTRICTED TO	
MATERIAL SEE CALLOUTS	FINISH	_	WEIGHT		A1	00779	C- 830126			
			CUSTOMER DE	RAWING			scale 2:1	SHEET OF	1 REV P1	

4805 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 1-830126-6