

## PCB terminal block - STB 3/4-5,08 - 1750045

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 16 A, Pitch: 5.08 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Color: green

### Key Commercial Data

Packing unit	50 pc
GTIN	 4 017918 028237
Weight per Piece (excluding packing)	14.14 g
Custom tariff number	85369010
Country of origin	Poland
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Pitch	5.08 mm
Pin dimensions	1 x 0,8 mm
Hole diameter	1.3 mm

#### General

Range of articles	STB
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	16 A
Nominal cross section	0 mm <sup>2</sup>
Solder pin surface	Sn
Stripping length	8 mm
Number of positions	4
Screw thread	M3

#### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	2.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

# PCB terminal block - STB 3/4-5,08 - 1750045

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490
eCl@ss 8.0	27440401

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002643

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

Approvals

CSA / UL Recognized / EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

CSA	
mm <sup>2</sup> /AWG/kcmil	28-14
Nominal current I <sub>N</sub>	10 A

# PCB terminal block - STB 3/4-5,08 - 1750045

## Approvals

Nominal voltage UN	300 V
--------------------	-------

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	30-14
Nominal current I <sub>N</sub>	10 A
Nominal voltage UN	300 V

EAC
-----

## Accessories

### Accessories

#### Coding element

Printed-circuit board connector - CS-STB - 1750142

Coding profile, for plugging into the coding ribs of the plug at a later date, insulating material, color: Red

---

## Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663



Insulating sleeve, Color: white

---

Insulating sleeve - MPS-IH RD - 0201676



Insulating sleeve, Color: red

## PCB terminal block - STB 3/4-5,08 - 1750045

### Accessories

Insulating sleeve - MPS-IH GN - 0201702



Insulating sleeve, Color: green

Insulating sleeve - MPS-IH BK - 0201731



Insulating sleeve, Color: black

### Labeled terminal marker

Marker pin Zack strip - BNB-ZB 5,LGS:FORTL.ZAHLEN - 1400201



Marker pin Zack strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Plug in, for terminal block width: 5.2 mm, Lettering field: 4 x 4 mm

### Terminal marking

Marker pin Zack strip - BN-ZB 5/WH:UNBEDRUCKT - 1400078



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Plug in, for terminal block width: 5 mm, Lettering field: 4 x 4 mm

### Test plug terminal block

Test plugs - MPS-MT - 0201744



Test plugs, Color: silver

## PCB terminal block - STB 3/4-5,08 - 1750045

### Accessories

Reducing plug - RPS - 0201647



Reducing plug, Color: gray

---

Phoenix Contact 2015 © - all rights reserved  
<http://www.phoenixcontact.com>