

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com


Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| | |
|------------|---|
| Type | ZDT 2.5/2 |
| Order No. | 1815150000 |
| Version | Z-series, Double-tier terminal, Rated cross-section: 2.5 mm ² , Tension clamp connection, Dark Beige |
| GTIN (EAN) | 4032248340774 |
| Qty. | 50 pc(s). |

Data sheet

Z-series ZDT 2.5/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------------------------|---------|-----------------|------------|
| Width | 5.1 mm | Width (inches) | 0.201 inch |
| Height | 80.5 mm | Height (inches) | 3.169 inch |
| Depth | 52 mm | Depth (inches) | 2.047 inch |
| Depth including DIN rail | 52.5 mm | Net weight | 9.67 g |

Temperatures

| | | | |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 120 °C |
|----------------------------------|--------|----------------------------------|--------|

Material data

| | | | |
|---------------------------|-------|--------|------------|
| Material | Wemid | Colour | Dark Beige |
| UL 94 flammability rating | V-0 | | |

System specifications

| | | | |
|-----------------------------------|--|----------------------------------|-----|
| Version | 2 tension-clamp connections - 2 plug-in connections, pluggable | End cover plate required | Yes |
| Number of levels | 2 | No. of clamping points per level | 4 |
| Levels cross-connected internally | No | PE connection | No |
| Mounting rail | TS 35 | | |

Additional technical data

| | | | |
|--------------------------|---------|------------|-------|
| Explosion-tested version | No | Open sides | right |
| Type of mounting | Snap-on | | |

CSA rating data

| | | | |
|-----------------------------------|----------------|-----------------------------------|--------|
| Certificate number (cCSAus) | 154685-1460993 | Current size C (cCSAus) | 20 A |
| Current size D (cCSAus) | 5 A | Voltage size C (cCSAus) | 300 V |
| Voltage size D (cCSAus) | 600 V | Wire cross section max. (cCSAusX) | 12 AWG |
| Wire cross section min. (cCSAusX) | 26 AWG | | |

Conductors for clamping (additional connection)

| | |
|---|---------------------|
| Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max. | 2.5 mm ² |
|---|---------------------|

Z-series
ZDT 2.5/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Conductors for clamping (rated connection)

| | | | |
|---|--------------------------|---|---------------------|
| Blade size | 0.6 x 3.5 mm | Clamping range, rated connection, max. | 4 mm ² |
| Clamping range, rated connection, min. | 0.13 mm ² | Connection direction | top |
| Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min. | 0.5 mm ² | Gauge to IEC 60947-1 | A2 |
| Number of connections | 4 | Stripping length | 10 mm |
| Type of connection | Tension clamp connection | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 26 | Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max. | 2.5 mm ² |
| Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min. | 0.5 mm ² | Wire connection cross section, finely stranded, max. | 4 mm ² |
| Wire connection cross section, solid core max. rated connection | 4 mm ² | Wire connection cross section, solid core, min. rated connection | 0.5 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max. | 2.5 mm ² | Wire connection cross-section, finely stranded, min. | 0.5 mm ² |

Rating data

| | | | |
|--|---------------------|---------------------------------|---|
| Rated cross-section | 2.5 mm ² | Rated voltage | 500 V |
| Max. voltage of clamp support & pluggable system | 690 V | Rated current | 24 A |
| Current at maximum wires | 24 A | Standards | IEC 61984, In accordance with IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 2.66 mΩ | Rated impulse withstand voltage | 6 kV |
| Pollution severity | 3 | | |

UL rating data

| | | | |
|--|--------|--|--------|
| Certificate No. (cURus) | E60693 | Conductor size Factory wiring max. (cURus) | 12 AWG |
| Conductor size Factory wiring min. (cURus) | 26 AWG | Conductor size Field wiring max. (cURus) | 12 AWG |
| Conductor size Field wiring min. (cURus) | 26 AWG | Current size C (cURus) | 20 A |
| Current size D (cURus) | 5 A | Voltage size C (cURus) | 300 V |
| Voltage size D (cURus) | 600 V | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000897 | ETIM 4.0 | EC000902 |
| ETIM 5.0 | EC000902 | ETIM 6.0 | EC000897 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-14-11-18 |
| eClass 6.2 | 27-14-11-26 | eClass 7.1 | 27-14-11-26 |
| eClass 8.1 | 27-14-11-26 | eClass 9.0 | 27-14-11-26 |
| eClass 9.1 | 27-14-11-20 | | |

Product information

| | |
|---------------------------------|---|
| Descriptive text technical data | 2.5 mm ² flexible wires with wire-end ferrules are crimped with the Weidmüller PZ 6/5 crimping tool. |
| Descriptive text accessories | ZVQ 2.5/1.5 (1720700000) connects the upper and lower layer. |

Creation date December 31, 2017 10:52:39 PM CET

Data sheet**Z-series
ZDT 2.5/2****Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com**Technical data****Approvals**

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[DE_PT1131_20160418_1134_ISSUE01.pdf](#)

Brochure/Catalogue

[CAT 1 TERM 16/17 EN](#)

Engineering Data

[EPLAN, WSCAD, Zuken E3.S](#)**Safety note**

Safety notice


[Safety Information](#)

Data sheet

Z-series
ZDT 2.5/2

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings



Data sheet

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

ZVQ 2.5/1.5



Spring connection with tension clamp Technology
 Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-------------|----------------------------|------------------------------|---------------|-----------|
| ZVQ 2.5/1.5 | 1720700000 | Accessories, Cross-connector | 4008190374006 | 50 pc(s). |

Locking element



Spring connection with tension clamp Technology
 Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|------------|----------------------------|--|---------------|-----------|
| ZVR ZPS2.5 | 1878620000 | Z-series, Locking clips, Yellow, 15 mm | 4032248471591 | 20 pc(s). |

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|------------|----------------------------|---|---------------|--------------|
| DEK 5/5 MC | 1609801044 | Dekafix, Terminal marker, | 4008190397111 | 1,000 pc(s). |
| NE WS | | 5 x 5 mm, Pitch in mm (P): 5,00 Weidmueller, White | | |

Strain relief



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-------------|----------------------------|---|---------------|-----------|
| ZZE ZP2.5 | 1816140000 | Z-series, Strain relief, Yellow, 9.9 mm | 4032248370719 | 25 pc(s). |
| ZZE ZP2.5/4 | 1866220000 | Z-series, Strain relief, Yellow, 19.9 mm | 4032248480845 | 25 pc(s). |

Data sheet

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

Test adapter



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|--------------|----------------------------|--------------------------------------|------------------|--------|
| ZTA ZT2.5/ZA | 1847600000 | Accessories, Test adapter, 17.5 A | 4032248412679 25 | pc(s). |
| ZTA ZT2.5 | 1827080000 | Accessories, Test adapter, 17.5 A | 4032248411276 25 | pc(s). |

End plates



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Available until | Type | Order No. | Version | GTIN (EAN) | Qty. |
|-----------------|------------------|----------------------------|--|------------------|--------|
| 1970-01-01 | ZAP11W1-ZDT2.5/2 | 1816110000 | Z-series, End plate, Seperation plate | 4032248370689 50 | pc(s). |

Z-series
ZDT 2.5/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories
2.5 mm²
Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. | |
|----------------------|----------------------------|--|----------------------------|---|--------------|
| ZP 2.5/1AN/ QV/9 | 1815270000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342556 | 20 pc(s). | |
| ZP 2.5/1AN/ QV/8 | 1815260000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342549 | 20 pc(s). | |
| ZP 2.5/1AN/ QV/10 | 1815280000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342563 | 20 pc(s). | |
| ZP 2.5/1AN/ QV/7 | 1815250000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342532 | 25 pc(s). | |
| ZP 2.5/1AN/ QV/6 | 1815240000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342525 | 25 pc(s). | |
| ZP 2.5/1AN/ QV/1 | 1815190000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248370061 | 50 pc(s). | |
| ZP 2.5/1AN/ QV/12 | 1815300000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342587 | 20 pc(s). | |
| ZP 2.5/1AN/ QV/11 | 1815290000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248342570 | 20 pc(s). | |
| ZP 2.5/1AN/ QV/16 | 1815340000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248370146 | 10 pc(s). | |
| ZP 2.5/1AN/ QV/14 | 1815320000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248370122 | 10 pc(s). | |
| ZP 2.5/1AN/ QV/3 | 1815210000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248370092 | 25 pc(s). | |
| Discontinued | 2016-03-30T00:00:00+02:00 | ZP 2.5/1AN/QV/20 | 1815380000 | Rail components, 4032248370184 Plug-in connector | 10 pc(s). |
| ZP 2.5/1AN/ QV/4 | 1815220000 | Z-series, Plug-in connector, Dark Beige, Direct mounting | 4032248370108 | 25 pc(s). | |

Z-series ZDT 2.5/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

| | | |
|------------------------|----------------------------|---|
| ZP 2.5/1AN/ QV/5 | 1815230000 | Z-series, Plug-in connector, 4032248342518 25 pc(s). Dark Beige, Direct mounting |
| ZP 2.5/1AN/ QV/13 | 1815310000 | Z-series, Plug-in connector, 4032248370115 10 pc(s). Dark Beige, Direct mounting |
| ZP 2.5/1AN/ QV/17 | 1815350000 | Z-series, Plug-in connector, 4032248370153 10 pc(s). Dark Beige, Direct mounting |
| ZP 2.5/1AN/ QV/2 | 1815200000 | Z-series, Plug-in connector, 4032248370085 25 pc(s). Dark Beige, Direct mounting |
| ZP 2.5/1AN/ QV/1 GN | 1820570000 | Z-series, Plug-in connector, 4032248370078 50 pc(s). Green, Direct mounting |
| ZP 2.5/1AN/ QV/15 | 1815330000 | Z-series, Plug-in connector, 4032248370139 10 pc(s). Dark Beige, Direct mounting |

Covers



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-------------------|----------------------------|--|-------------------------|------|
| ZAD ZT/ ZPS2.5 | 1861030000 | Z-series, cover plate, Yellow, 4.2 mm | 4032248418428 25 pc(s). | |

Locking strap



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|----------------------|----------------------------|---|-------------------------|------|
| ZVLA SC ZPS2.5 | 1866240000 | Z-series, Plug-in modular terminals, Yellow, 15 mm | 4032248513376 20 pc(s). | |
| ZVLA DF CL ZPS2.5 | 1878610000 | Z-series, Plug-in modular terminals, Yellow | 4032248471584 20 pc(s). | |

Creation date December 31, 2017 10:52:39 PM CET

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

| | | | |
|--------------|----------------------------|---|-------------------------|
| ZVLA RC | 1866260000 | Z-series, Plug-in modular terminals, Yellow, 8.8 mm | 4032248524754 20 pc(s). |
| ZPS2.5 | | | |
| ZVLA1 ZPS2.5 | 1866250000 | Z-series, Plug-in modular terminals, Yellow, 8.8 mm | 4032248524761 20 pc(s). |

Blank



ZS markers - in proven MultiCard-format - have been developed specifically for the Z-series. They have a large printing area. The hinged mechanism even allows access to cross-connectors without dismantling. Quick installation is guaranteed by the fact that the single tags are clipped on in strips. The single tags are easy to separate.

- Hinged marker area
- Can be fitted in strips or individually
- Markers in proven MultiCard format

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|------------|----------------------------|---|---------------|------------|
| ZS 10/5 MC | 1610000000 | ZS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 | 4008190263171 | 480 pc(s). |
| NE WS | | Weidmueller, Allen-Bradley, White | | |

Coding/ locking element



Extensive range of accessories for the FieldPower® boxes. Cable seals, plug-in connectors, locking elements and much more.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|------------|----------------------------|--|---------------|-----------|
| KOSF ZT2.5 | 1816150000 | Z-series, Coding element, Yellow, 2.9 mm | 4032248370726 | 50 pc(s). |
| ZVR ZP2.5 | 1816130000 | Z-series, Locking clips, Yellow, 3.9 mm | 4032248370702 | 25 pc(s). |

Data sheet

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories

Tools



Tools for removing the sheathing of uncut power cables and outgoing feeders, plus screwdrivers for installing FieldPower components.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|--------------------|----------------------------|--|---------------|----------|
| SDS 0.6X3.5X100 | 9008330000 | Screwdriver, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade thickness (A): 0.6 mm | 4032248056286 | 1 pc(s). |

STR transparent strips



The various terminal markers from Weidmüller enable users to solve virtually every labelling task on all types of lines. Whether several lines of labelling, ready-to-use markers with standard printing, or individual labelling, whether white or coloured markers or common designations at the clamping points, the comprehensive range of products represent the easy, quick and clear answer to every marking task.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-------------------|----------------------------|--|---------------|-----------|
| STR 7 F.SCHT 7 | 0515300000 | Terminal markers, Protective cap, 27 x 6.3 mm, Transparent | 4008190182175 | 20 pc(s). |

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories
ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|------------|----------------------------|---|---------------|-----------|
| ZGB 15 | 1636530000 | Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00 White | 4008190297053 | 20 pc(s). |
| ZGB 30 | 1611930000 | Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00 White | 4008190002251 | 20 pc(s). |
| ZGB 30/3.5 | 1778290000 | Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 3.50 White | 4032248161065 | 20 pc(s). |

Blank


WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-----------------------|----------------------------|---|---------------|------------|
| WS 10/5 M MC NE WS | 1792000000 | WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, Allen-Bradley, White | 4032248223862 | 720 pc(s). |

**Z-series
ZDT 2.5/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories
ZQV 2.5N

Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| Type | Order No. | Version | GTIN (EAN) | Qty. |
|-------------------|----------------------------|------------------------------------|---------------|-----------|
| ZQV 2.5N/10 GE | 1693880000 | Z-series, Cross-connector, 24 A | 4008190883720 | 20 pc(s). |
| ZQV 2.5N/4 GE | 1693820000 | Z-series, Cross-connector, 24 A | 4008190883652 | 60 pc(s). |
| ZQV 2.5N/50 GE | 1693890000 | Z-series, Cross-connector, 24 A | 4008190883737 | 5 pc(s). |
| ZQV 2.5N/5 GE | 1693830000 | Z-series, Cross-connector, 24 A | 4008190883669 | 20 pc(s). |
| ZQV 2.5N/8 GE | 1693860000 | Z-series, Cross-connector, 24 A | 4008190883690 | 20 pc(s). |
| ZQV 2.5N/3 GE | 1693810000 | Z-series, Cross-connector, 24 A | 4008190883645 | 60 pc(s). |
| ZQV 2.5N/7 GE | 1693850000 | Z-series, Cross-connector, 24 A | 4008190883683 | 20 pc(s). |
| ZQV 2.5N/9 GE | 1693870000 | Z-series, Cross-connector, 24 A | 4008190883706 | 20 pc(s). |
| ZQV 2.5N/6 GE | 1693840000 | Z-series, Cross-connector, 24 A | 4008190883676 | 20 pc(s). |
| ZQV 2.5N/20 GE | 1909000000 | Z-series, Cross-connector, 24 A | 4032248535613 | 20 pc(s). |
| ZQV 2.5N/2 GE | 1693800000 | Z-series, Cross-connector, 24 A | 4008190883621 | 60 pc(s). |