



Rated cross-section ≤ 2.5 mm²



LP 7.50/90



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	26	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 59

Solder pin length	3.2 mm	4.5 mm
Colour		



Poles	Type	Cat. No.	Cat. No.	Qty.
2	LP 7.50/2/90	1594420000	1697220000	100
3	LP 7.50/3/90	1594430000	1697230000	100

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	46

LPP 7.50/90



with test point



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	26	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 59

Solder pin length	3.2 mm	4.5 mm
Colour		



Poles	Type	Cat. No.	Cat. No.	Qty.
2	LPP 7.50/2/90	1594440000	1697260000	100
3	LPP 7.50/3/90	1594450000	1697270000	100

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	43, 46

LP 7.50/135



with test point



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	26	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 59

Solder pin length	3.2 mm	4.5 mm
Colour		

Poles	Type	Cat. No.	Cat. No.	Qty.
2	LP 7.50/2/135	1595770000	1697300000	100
3	LP 7.50/3/135	1595810000	1697310000	100

Accessories	Page
Marking	40
Fixing	-
Miscellaneous	46

Rated cross-section ≤ 2.5 mm²