







LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		A	ECO-07-019301	23AUG07	MB	DR





SWITCH FUNCTION D1
CIRCUIT DIAGRAM



SWITCH FUNCTION D2
CIRCUIT DIAGRAM





PANEL CUT OUT






1977069-2 SHOWN

2.00-4.00[.079-.158]	19.8-0.1 [.780-.004]	13.0+0.1 [.512+.004]
1.25-2.00[.049-.079]	19.4-0.1 [.764-.004]	13.0+0.1 [.512+.004]
0.75-1.25[.030-.049]	19.2-0.1 [.756-.004]	13.0+0.1 [.512+.004]
PANEL THICKNESS	X	Y

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER	03APR2007	Tyco Electronics Corporation Harrisburg, Pa 17105-3608		
DIMENSIONS: mm [INCHES]		CHK D.ROHDE	-			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	-	NAME POWER ROCKER SWITCH, 13.0mm X 19.2mm		
0 PLC ± -		PRODUCT SPEC	-	PANEL CUT-OUT SIZE, DOUBLE POLE,DOUBLE THROW,		
1 PLC ± 0.30[.012]		APPLICATION SPEC	-	SIX TERMINALS, NON-ILLUMINATED		
2 PLC ± 0.05[.002]		NOT APPLICABLE	-	SIZE	CAGE CODE	DRAWING NO
3 PLC ± -		NOT APPLICABLE	-	A2	00779	C=1977069
4 PLC ± -		NOT APPLICABLE	-	RESTRICTED TO	-	
ANGLES ± -		WEIGHT	-	SCALE	3:1	SHEET 1 OF 3
FINISH		CUSTOMER DRAWING	-	REV	A	



PANEL CUT OUT



1-1977069-1 SHOWN

2.00–4.00[.079–.158]	19.8–0.1 [.780–.004]	13.0+0.1 [.512+.004]
1.25–2.00[.049–.079]	19.4–0.1 [.764–.004]	13.0+0.1 [.512+.004]
0.75–1.25[.030–.049]	19.2–0.1 [.756–.004]	13.0+0.1 [.512+.004]
PANEL THICKNESS	X	Y

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER	03APR2007	 Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm [INCHES]		CHK D.ROHDE	-	NAME	
		APVD	-	POWER ROCKER SWITCH, 13.0mm X 19.2mm PANEL CUT-OUT SIZE, DOUBLE POLE, DOUBLE THROW, SIX TERMINALS, NON-ILLUMINATED	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± 0.30[.012] 2 PLC ± 0.05[.002] 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC	-	SIZE	
		APPLICATION SPEC	-	CAGE CODE	DRAWING NO
		RESTRICTED TO	-	A2 00779 C-1977069	
MATERIAL		WEIGHT	-	CUSTOMER DRAWING	
		FINISH		SCALE	SHEET
				3:1	2 OF 3
				REV	A

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

LEGACY PART NUMBER

X₁X₂

X₃

X₄

X₅X₆

X₇X₈

X₉

X₁₀

X₁₁

X₁₂

X₁₃

X₁₄

SWITCH TYPE: X₁X₂ = PR - POWER ROCKER

SECONDARY ROCKER COLOR: X₁₂ = Ø - NOT APPLICABLE

NOMINAL PANEL CUT OUT SIZE: X₃ = A - 13.0x19.2[.512x.756]

NUMBER OF POLES: X₄ = D - DOUBLE

SWITCH FUNCTION: X₅X₆ =

D1: ON-ON, WITH OPAQUE, SINGLE COLOR ROCKER BUTTON

D2: ON-(ON), WITH OPAQUE, SINGLE COLOR ROCKER BUTTON

D3: ON-OFF-ON, WITH OPAQUE, SINGLE COLOR ROCKER BUTTON

D4: ON-OFF-(ON), WITH OPAQUE, SINGLE COLOR ROCKER BUTTON

CURRENT RATING: X₇X₈ = 12 - △6

LEGEND TEXT PATTERN: X₁₃ =

Ø

D

E

F

G

- =

I II

- O =

I O II

TERMINAL TYPE: X₉ = E - QC TAB

FRAME COLOR: X₁₀ =

B - BLACK

W - WHITE

ROCKER COLOR: X₁₁ =

B - BLACK

G - GREEN

R - RED

W - WHITE

LEGEND TEXT COLOR: X₁₄ =

Ø - NOT APPLICABLE

G - GREEN

R - RED

B - BLACK

W - WHITE

1

MATERIALS:

ROCKER BUTTON & HOUSING FRAME: NYLON 66, UL 94 V-2.

TERMINAL, ACTIVE CONTACTOR: COPPER ALLOY PER ASTM B152/B152M

PLUNGER: BRASS PER ASTM B036

SPRING: STEEL WIRE PER ASTM A228/A228M

2

FINISH:

PLUNGER: 1.02µm[.000040]MIN NICKEL

3

ELECTRICAL SPECIFICATIONS:

CURRENT AND VOLTAGE: △6

CONTACT RESISTANCE: (INITIAL): <100mΩ

DIELECTRIC STRENGTH (INITIAL): >1000 VAC, 1 MINUTE

INSULATION RESISTANCE (INITIAL): >100MΩ (500 VDC BETWEEN OPEN CONTACTS)

ELECTRICAL LIFE ENDURANCE: >6000 OPERATIONS, VOLTAGE DROP: <100mV

TEMPERATURE RISE AT TERMINALS: <30°C, 6000 OPERATIONS

(AMBIENT CONDITIONS: 25±2°C AND 65±5%R.H)

4

MECHANICAL SPECIFICATIONS:

ACTUATING FORCE: 400g MIN, 1400g MAX

OPERATING LIFE ENDURANCE: >100,000 OPERATIONS

TERMINAL RETENTION FORCE: >6.8kg- QC TAB

5

ENVIRONMENTAL SPECIFICATIONS:

AMBIENT TEMPERATURE: -20°C TO +85°C

HUMIDITY: MAX 85%

SALT SPRAY: NO REMARKABLE RUST ON METAL PARTS

(5% SALT/ 35°C, 24HRS)

SHOCK: NO MECHANICAL DEFECT OR DAMAGE

(500G 11MSEC / X,Y,Z, 3 TIMES)

6

12A@125VAC/6A@250VAC

7

ELECTRICAL RATINGS, APPROVED AGENCY LOGOS, TERMINAL IDENTIFICATION NUMBERS, AND THE TE LOGO MOLDED APPROXIMATELY AS SHOWN ON THE SIDES OF THE SWITCH HOUSING.

8

COMPONENT RECOGNIZED TO US & CANADIAN STANDARDS, UL FILE NO. E46765.

9

ROHS 2002/95/EC COMPLIANT.

2	PRADD4-12F-BB0GW	1-1977069-2
2	PRADD4-12F-BB0FW	1-1977069-1
2	PRADD4-12F-BB000	1-1977069-0
1	PRADD2-12F-BB0EW	1977069-9
1	PRADD2-12F-BB0DW	1977069-8
1	PRADD2-12F-BB000	1977069-7
2	PRADD3-12F-BB0GW	1977069-6
2	PRADD3-12F-BB0FW	1977069-5
2	PRADD3-12F-BB000	1977069-4
1	PRADD1-12F-BB0EW	1977069-3
1	PRADD1-12F-BB0DW	1977069-2
1	PRADD1-12F-BB000	1977069-1
SHEET REF	LEGACY PART NUMBER	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN M.BINNER

CHK D.ROHDE

APVD -

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± 0.30[.012]

2 PLC ± 0.05[.002]

3 PLC ± -

4 PLC ± -

ANGLES ± -

MATERIAL △1

FINISH △2

03APR2007

PRODUCT SPEC

NOT APPLICABLE

APPLICATION SPEC

NOT APPLICABLE

WEIGHT -

CUSTOMER DRAWING

Tyco Electronics

Tyco Electronics Corporation

Harrisburg, Pa 17105-3608

NAME

POWER ROCKER SWITCH, 13.0mm X 19.2mm

PANEL CUT-OUT SIZE, DOUBLE POLE,DOUBLE THROW,

SIX TERMINALS, NON-ILLUMINATED

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A200779

C=1977069

-

SCALE

3:1

SHEET

3

OF

3

REV

A

AMP 1471-9 REV 31MAR2000

1977069