



Rated cross-section ≤ 2.5 mm²



LP 10.00/90



Technical Data		VDE	UL	CSA
Rated voltage	V	630*	300	300
Rated current	A	26	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3

Additional technical data see page 60



Solder pin length **3.2 mm**



Colour			
Poles	Type	Cat. No.	Qty.
2	LP 10.00/2/90	1693650000	50
3	LP 10.00/3/90	1693660000	50
4	LP 10.00/4/90	1692700000	50

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	45

LP 15.00/90



Technical Data		VDE	UL	CSA
Rated voltage	V	1000	600	600
Rated current	A	27	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3

Additional technical data see page 60

Solder pin length **4.5 mm**



Colour			
Poles	Type	Cat. No.	Qty.
2	LP 15.00/2/90	1697550000	100
3	LP 15.00/3/90	1697560000	50
4	LP 15.00/4/90	1697570000	50

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	45