



Rated cross-section ≤ 2.5 mm²





LP 5.08/90





LPP 5.08/90

with test point



LP1N 5.08/90



Technical Data		VDE	UL	CSA
Rated voltage	V	250*	300	300
Rated current	A	25	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 58

Technical Data		VDE	UL	CSA
Rated voltage	V	250*	300	300
Rated current	A	25	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 58

Technical Data		VDE	UL	CSA
Rated voltage	V	250*	300	300
Rated current	A	24	15	15
Clamping range max.	mm ² /AWG	4.0	12	12

*Overvoltage category III / Pollution severity 3
Additional technical data see page 58

Solder pin length		3.2 mm	4.5 mm	
Colour				
Poles	Type	Cat. No.	Cat. No.	Qty.
1	LP 5.08/1/90	1730300000	-	100
2	LP 5.08/2/90	1592820000	1696040000	100
3	LP 5.08/3/90	1592830000	1696050000	100
4	LP 5.08/4/90	1594360000	-	50
6	LP 5.08/6/90	1608250000	-	50
8	LP 5.08/8/90	1594370000	-	50
10	LP 5.08/10/90	1594380000	-	50
12	LP 5.08/12/90	1608270000	-	50
16	LP 5.08/16/90	1594390000	-	50
24	LP 5.08/24/90	1608290000	-	20

Solder pin length		3.2 mm	4.5 mm	
Colour				
Poles	Type	Cat. No.	Cat. No.	Qty.
2	LPP 5.08/2/90	1594400000	1697120000	100
3	LPP 5.08/3/90	1594410000	1697130000	100

Solder pin length		3.2 mm	4.5 mm	
Colour				
Poles	Type	Cat. No.	Cat. No.	Qty.
2	LP1N 5.08/2	1640830000	1698030000	100
3	LP1N 5.08/3	1640840000	1698040000	100

See also page 47 "Application Examples LP System"

Attention: Customers are advised to ensure support for LP1N on the printed circuit board.

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	43-46

Accessories	Page
Marking	40
Fixing	46
Miscellaneous	43-46

Accessories	Page
Marking	40
Fixing	-
Miscellaneous	43, 45, 46

Rated cross-section ≤ 2.5 mm²