




TACTILE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

FSMRA2JHA04=R/A,TACT PB SW,260

[Alcoswitch](#) | [FSMRAJ](#)

1825027-6

TE Internal Number: 1825027-6

Alias ID: FSMRA2JHA

[Always EU RoHS/ELV Compliant](#)

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

[MICRO-MINIATURE PUSHBUTTON SWITCH](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1825027-6_05242013218_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Actuator Style

Round

Dust Proof

No

Lock Style

Unlocked

	Leg Style	Rinked
	Illuminated	With
	Product Type	Switch
Configuration Features	Operating Function	No
	Support Bracket	With
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	ESD Grounding Terminal	Without
	Ganged	With
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With
Body Features	Actuator Color	Red
	Bushing Style	Unthreaded
	Actuator Material	PBT
	Actuator Force	260 g [9.178 oz]
	Actuator Profile	Extended
	Case Color	Black
	Body Style	Right Angle
	Case Material	Nylon
Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50
Termination Features	Termination Type	Printed Circuit Board
Mechanical Attachment	Mounting Type	Through Hole
	Mounting Angle	Right Angle
Housing Features	Low Profile	With
	Process Sealed	No
Dimensions	Actuator Length	1.24 mm [.049 in]
	Switch Height	7 mm [.276 in]

Button Width

3.5 mm [.138 in]

Usage Conditions

Temperature Rating (°C)

Standard

Packaging Features

Packaging Method

Loose Piece

Other

Comment













(On) indicates momentary position.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

SPLICES	TACTILE SWITCHES	CRIMP RINGS & SPADES	SURFACE MOUNT RESISTORS
			
SPLICE, N CE 22-10 53915-1	FSMRA3JH04=R/A, TACT PB SW, 160G 1825027-8	RING IS 20-18 8 .020TPBR 40698	3521 82R 1% 2W 352182RFT
 Save to List	 Save to List	 Save to List	 Save to List
 Find Similar Products	 Find Similar Products	 Find Similar Products	 Find Similar Products