

CATALOG LISTING

12TS115 SERIES CHART 1

ISSUE 14

REVISIONS

A	0380402	JALA	178	93
B	0093667	JAT	26	JAN 99
C	95303	CS	15	NOV 99
D	203418	CS	25	JUN 01
E	0001095	JAH	12	AUG 02

DRAWN D B W I S

OCT 72

**MICRO SWITCH**  
MILWAUKEE, WISCONSIN, U.S.A.  
A DIVISION OF HONEYWELL

**SWITCH-TOGGLE**

CATALOG LISTING  
**12TS115 SERIES**  
**CHART 1**

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CAT. LIST.	CIRCUIT WITH TOGGLE IN			ELECTRICAL DATA	RELEASE NO.
	EXTREME POSITION KEYWAY 1-2	CENTER 4-5	EXTREME POSITION OPPOSITE 2-3 5-6		
12TS115-1	ON	OFF	ON	L312 10A 277 VAC, 20A 125 VAC 1 1/2 HP 125, 250 VAC	SR-5080
12TS115-2	OFF	NONE	ON		SR-5081
12TS115-3	ON	NONE	ON		SR-5082
(B)	NONE	OFF	ON		ETS
12TS115-5	MOM ON	OFF	ON		SR-5085
(C)	MOM ON	NONE	OFF		SR-5086
(D)	MOM ON	OFF	MOM ON		SR-5087
12TS115-8	MOM ON	NONE	ON		SR-5088
(E)	MOM OFF	NONE	ON	ETS	
(B)	MOM ON	OFF	NONE	ETS	

LOCKWASHER

LOCKING RING

2X HEX NUT

.072 ± .010 WIDE X .038 ± .010 DEEP KEYWAY

30° ± 8° TOTAL TRAVEL

15° ± 4°

BRIGHT NICKEL PLATED LEVER

SEALED TO PREVENT ENTRANCE OF LIQUIDS OR DUST

15/32 - 32 UNS THREAD TO WITHIN .060 OF SHOULDER

Ø .236

.85 ± .05

.47

1.062 MAX

Ø .10 HOLE IN TERMINALS

.19

1.310 ± .025  
-.015

.75 ± .02

3 2 1

6 5 4

**NOTES**

1 - FURNISHED UNASSEMBLED

2 - VISUAL DIFFERENCES IN TERMINAL SHAPES AND PLATING POSSIBLE

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED

DIMENSIONS ARE IN INCHES

**TOLERANCES ARE:**

ONE PLACE ± .01     ± .030

TWO PLACE ± .001     ± .015

THREE PLACE ± .000     ± .005

ANGLES ±

WEIGHT .10 LB MAX