



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP72V28RT-3U

BP72V28RT-3U - External Battery Pack for UPS System

Highlights

- Extends the runtime of select compatible Tripp Lite UPS systems with 72VDC external battery connector
- Simple installation; 3U rackmount, tower and stack adaptable



Description

BP72V28RT-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. Additional DC connector enables the daisy-chaining of multiple external battery packs for longer extended run capability. COMPATIBLE UPS SYSTEMS - SMART3000RMOD2U, SU3000RTXL2U, SU3000RTXL3U, SU3000RTXL3UHV, SU3000RTXR3U, SU3000RTXR3UHW, SUINT3000RTXL2U, SUINT3000RTXL3U, SU3000XL and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP72V28RT-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation

Specifications

BATTERY	
Expandable battery runtime	Yes, DC connector accepts daisy-chaining of multiple external battery packs for extended runtime operation
DC system voltage (VDC)	72
Connects to UPS via	Black 3-point DC connector

Typical battery lifespan	4-6 years typical
PHYSICAL	
Shipping Dimensions (HWD/in)	11.25 x 23 x 33
Shipping Dimensions (HWD/cm)	28.58 x 58.42 x 83.8
Shipping weight (lbs)	164.8
Shipping weight (kg)	74.8
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.33 x 44.45 x 63.5
Unit weight (lbs)	148
Unit weight (kg)	66.6
Material of construction	Steel
Form factors supported	3U rack/tower
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
WEXT3-BP72V	3-Year Extended Warranty - For All 72V Battery Packs	1
WEXT5-BP72V	5-Year Extended Warranty - For All 72V Battery Packs	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3130.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.