

NetCommander PS2 Server Interface Unit (SIU)

MODEL NUMBER: **B078-101-PS2**



Description

Tripp Lite's NetCommander PS/2 Server Interface Unit (SIU) connects to the HD15 port and PS/2 ports on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cables can then be used to connect the computer/server to the switch ports on a Tripp Lite B070 / B072-Series NetCommander Cat5 KVM switch. Use of Cat5e cables frees up space in the installation that would be filled by traditional, thicker KVM cables.

Features

- Needed to connect a PS/2 Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100ft away from the KVM switch
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N

Highlights

- Needed to connect a PS/2 Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply needed
- Allows a recommended maximum distance of 100ft from KVM to Server via Cat5e cable
- Compact and lightweight design

System Requirements

- Server or CPU with a HD15 port and (2) PS/2 type connections
- A B070 / B072-Series NetCommander Cat5 KVM Switch
- Cat5e/6 cable; up to 100ft
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N

Package Includes

- (x1) B078-101-PS2 PS/2 Server Interface Unit (SIU)

Specifications

| OVERVIEW | |
|------------------|-----------------------|
| UPC Code | 037332148438 |
| Accessories Type | Server Interface Unit |
| INPUT | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|---|
| Bus Powered | Yes |
| Product Length (ft.) | 1.2 |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | GREEN (RECEIVING POWER); ORANGE (SELECTED AS ACTIVE PORT) |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 1.100 x 5.120 x 5.900 |
| Shipping Dimensions (hwd / cm) | 2.79 x 13.00 x 14.99 |
| Shipping Weight (lbs.) | 0.2400 |
| Shipping Weight (kg) | 0.11 |
| Unit Weight (lbs.) | 0.22 |
| Unit Weight (kg) | 0.10 |
| Material of Construction | ABS |
| Color | Gray |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 to 158 F (-20 to 70 C) |
| Storage Temperature Range | -4 to 158 F (-20 to 70 C) |
| CONNECTIONS | |
| Side A - Connector 1 | HD15 (MALE) |
| Side A - Connector 2 | (2) MINI DIN-6 (FEMALE) |
| Side B - Connector 1 | RJ45 (FEMALE) |
| Computer Keyboard and Mouse Interface | PS/2 |
| Computer Monitor Interface | VGA |
| FEATURES & SPECIFICATIONS | |
| Driver Required | No |
| Recommended Category Cable | N105 - SERIES CAT5E SHIELDED CABLES |
| CERTIFICATIONS | |
| Certifications | Tested to EN55022/EN55024, CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>