


## Product information

### BAT-ANT-N-MiMo5-9N-IP65

Industrial Ethernet:Industrial Wireless LAN:Accessories:Antenna:BAT-ANT-N-MiMo5-9N-IP65

Name	BAT-ANT-N-MiMo5-9N-IP65
	
	5 GHz MiMo antenna for sectoral illumination
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	5 GHz MiMo antenna for sectoral illumination
Type	BAT-ANT-N-MiMo5-9N-IP65
Order No.	943 981-013
Cable length	3 x 90 cm directly attached
Cable specification	N-plug
<b>Radio technology</b>	
Range	please refer to the antenna distance calculator
Frequency band	5150 MHz - 5875 MHz
Polarisation	triple linear, 45° slant
Elevation, Azimuth	3 dB beam width 60° / 60°
VSWR	1.5
Gain	9 dBi
Antenna connector	N male
<b>Ambient conditions</b>	
Operating temperature	-40 °C to +80 °C
Storage/transport temperature	-40 °C to +80 °C
Wind load	15 N at 160 km/h
<b>Mechanical construction</b>	
Dimensions (W x H x D)	101 mm x 80 mm x 35 mm
Mounting	wall, mast
Protection class	IP65
Material	LEXAN EXL 9330
Weight	0.11 kg
<b>Scope of delivery and accessories</b>	
Scope of delivery	antenna, mounting material, 3x pigtail N to RP-SMA

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.  
 The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.