

MECHANICAL DETAILS

Shell Style Model BRR* : Cap spring loaded dust cap for ERA ERN and EG receptacle or PSA and PK fixed receptacle

Keying

Housing Material PSU (Polysulfone) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing 0 - 0 mm

Variant 2 G : Grey

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								

PERFORMANCE DETAIL

Insert :

Insulator

Insulator









OTHER CHARACTERISTICS

- Endurance (Shell)** Endurance (Shell):
- Temp (min)** -50°C
- Temp (max)** +150°C
- Humidity (max):** <=95% [at 60 deg C /140 F]
- Vibration:** 15 g [10 Hz - 2000 Hz]
- Shock Resistance:** 100 g [6 ms]
- Salt Spray** >144 hr
- Climatical** 50/175/21
- Shielding (min):** 75 dB (10 MHz)
- Shielding (min):** 40 dB (1 GHz)
- IP Rating** 50

Available Download

 [Coax_triax_mixed_en.pdf](#)

Related links

-  [Contact](#)
-  [Quote Request](#)
-  [Catalogs Downloads](#)
-  [Catalogs Requests](#)
-  [Sample Request](#)
-  [3D drawings](#)