LP3R 5.08/90

triple level





Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	20	15	20
Wire size (mm²/AWG)	4.0	26…12	26…12

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 58

Solder pin length	4.5 mm	4.5 mm	
Color			
Poles	Type	Part No.	Part No.	Qty.
6	LP3R 5.08/6/90	**1653940000**	**1695940000**	50
9	LP3R 5.08/9/90	**1596330000**	**1695950000**	50
12	LP3R 5.08/12/90	**1596350000**	-	
15	LP3R 5.08/15/90	**1596370000**	-	
18	LP3R 5.08/18/90	**1596390000**	-	
21	LP3R 5.08/21/90	**1633010000**	-	
24	LP3R 5.08/24/90	**1596410000**	-	
27	LP3R 5.08/27/90	**1633020000**	-	
30	LP3R 5.08/30/90	**1596430000**	-	
33	LP3R 5.08/33/90	**1633030000**	-	
36	LP3R 5.08/36/90	**1633040000**	-	
39	LP3R 5.08/39/90	**1633050000**	-	
42	LP3R 5.08/42/90	**1633060000**	-	
45	LP3R 5.08/45/90	**1633070000**	-	
48	LP3R 5.08/48/90	**1633080000**	-	
51	LP3R 5.08/51/90	**1633090000**	-	
54	LP3R 5.08/54/90	**1633100000**	-	
57	LP3R 5.08/57/90	**1633110000**	-	
60	LP3R 5.08/60/90	**1633120000**	-	
63	LP3R 5.08/63/90	**1633130000**	-	
66	LP3R 5.08/66/90	**1633140000**	-	
69	LP3R 5.08/69/90	**1633150000**	-	
72	LP3R 5.08/72/90	**1633160000**	-	

Accessories	Page
Marking	40
Mounting	46
Miscellaneous	43, 45

LPTR 5.08/90

new

with 2 test points

with disconnect knife





Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	20	15	20
Wire size (mm²/AWG)	4.0	26…12	26…12

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 58

Solder pin length	4.5 mm	4.5 mm	
Color			
Poles	Type	Part No.	Part No.	Qty.
1	LPTR 5.08/1/90	**1755230000**	**1755190000**	100

With adaptor plate LPZP 2.54/90 (Part No. **1747480000**) it is possible to create the pitch 7.62 mm.

See also page 47 **"Application Examples for LP Series"**

Accessories	Page
Marking	40
Mounting	46
Miscellaneous	45-46

LPZF 5.08/180





Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	17.5	10	18
Wire size (mm²/AWG)	2.5	26…14	14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 55

Solder pin length	3.2 mm	4.5 mm	
Color			
Poles	Type	Part No.	Part No.	Qty.
2	LPZF 5.08/2/180	**1698450000**	**1698560000**	100
3	LPZF 5.08/3/180	**1698460000**	**1698570000**	100
4	LPZF 5.08/4/180	**1698470000**	**1698580000**	100
5	LPZF 5.08/5/180	**1698480000**	**1698590000**	50
6	LPZF 5.08/6/180	**1698490000**	**1698600000**	50
7	LPZF 5.08/7/180	**1698500000**	**1698610000**	50
8	LPZF 5.08/8/180	**1698510000**	**1698620000**	50
9	LPZF 5.08/9/180	**1698520000**	**1698630000**	25
10	LPZF 5.08/10/180	**1698530000**	**1698640000**	25
11	LPZF 5.08/11/180	**1698540000**	**1698650000**	25
12	LPZF 5.08/12/180	**1698550000**	**1698660000**	25

Design compatible with LMT 5.08/180 on page 21

Accessories	Page
Marking	42
Mounting	-
Miscellaneous	45