

1520137 -1 Product Details



1520137 -1

[Active](#)

Power Toggle Switches

[RoHS Compliant](#) (Statement of Compliance)

Product Highlights:

- ? Double Pole - Single Throw Configuration (Pole - Throw)
- ? Toggle Length = 12.70 mm
- ? Toggle Style = Baton with Ball
- ? Bushing Length = 10.41 mm
- ? Termination Type = Screw -In Terminal

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? None Available

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Configuration (Pole - Throw) = Double Pole - Single Throw
- ? Termination Type = Screw -In Terminal

Electrical Characteristics:

- ? UL/CSA 250V Current Rating (Amps.) = 20
- ? UL/CSA 125V Horse Power Rating (hp) = 1.50
- ? UL/CSA 250V Horse Power Rating (hp) = 2.00

Housing Related Features:

- ? Toggle Length (mm [in]) = 12.70 [0.500]
- ? Toggle Style = Baton with Ball

Configuration Related Features:

- ? Bushing Length (mm [in]) = 10.41 [0.410]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Not reviewed for lead free solder process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- ? Brand = Alcoswitch