



**NOTES**

- 1 - MOUNTING HOLES WILL ACCEPT  $\phi .087$  MAX PINS OR SCREWS ON  $.188 \pm .002$  CENTERS
- 2 - ACTUATION IN LINE WITH ARROW "A" IS RECOMMENDED
- 3 - WEIGHT OF SWITCH ONLY IS  $.16$  OZ MAX. WEIGHT OF SWITCH WITH WIRE LEADS IS  $.40$  OZ MAX
- 4 - CONTACT MATERIAL: 24K SOLID GOLD
- 5 - YELLOW MARKING IS ON BOTH SIDES OF HOUSING TO IDENTIFY THAT THIS UNIT HAS GOLD CONTACTS

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



CHARACTERISTICS		ELECTRICAL DATA	
OPERATING FORCE	5-17 OZ	CONTACT ARRANGEMENT	
RELEASE FORCE	4 OZ MIN	S P D T	
RELEASE TRAVEL	.004 MIN	28 VOLTS DC RATING	
DIFFERENTIAL TRAVEL	.005 MAX	INDUCTIVE	
OVERTRAVEL	.004 MIN	RESISTIVE	
		SEA LEVEL	
		50,000 FT	
		SEA LEVEL	
		50,000 FT	
		1 AMP	
		50,000 FT	
		1 AMP	
		SCALE	
		2 : 1	
		SCALE PRINT	
		DO NOT	
		UNLESS OTHERWISE SPECIFIED	
		TOLERANCES ARE	
		ONE PLACE (.0)	
		TWO PLACE (.00)	
		THREE PLACE (.000)	
		ANGLES	
		±	
		WEIGHT	
		3	

1XE315  
CATALOG LISTING

ISSUE A

REVISIONS

CHECK

16 DEC 03

16 DEC 03

M D M

RELEASE NO. 0002632

PAGE 1 OF 1

REPLACES