

12SE4-2

CATALOG LISTING

PAGE 1 OF 1

REPLACES

PR-3929

RELEASE NO.

M

ISSUE
8

CHECK

CHECK

5 MAR 99

J A F


CHECK

5 MAR 99

J J A

FORMTEK

DRAWN




NOTES

- ① MOUNTING HOLES WILL ACCEPT PINS AND SCREWS OF $.087$ MAX DIA ON $.375 \pm .002$ CENTERS
- ② ACTUATION IN LINE WITH ARROW "A" IS RECOMMENDED
- ③ WEIGHT OF SWITCH ONLY IS $.26$ OZ MAX, WEIGHT OF SWITCH WITH WIRE LEADS IS 1.30 OZ MAX
- ④ WIRE LEADS MARKED WITH CIRCUIT IDENTIFICATION AND WIRE GAGE (CLOSED-20, OPEN-20, AND COMMON-20) PER MIL-W-5088

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE ----- **5-19 OZ**
RELEASE FORCE ----- **4 OZ MIN**
RELEASE TRAVEL ----- **.004 MIN**
DIFFERENTIAL TRAVEL --- **.004 MAX**
OVERTRAVEL ----- **.003 MIN**

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

SCALE **FULL**

DO NOT
SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE (.) $\pm .030$

TWO PLACE (.00) $\pm .015$

THREE PLACE (.000) $\pm .005$

ANGLES \pm

WEIGHT **③**

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[12SE4-2](#)