



General ordering data

| | |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Order No. | 1769280000 |
| Part designation | LM2H5.08/12 3.5 OR |
| Version | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 12, 90°, Box |
| EAN | 4032248116331 |
| Qty. | 20 pc(s). |

System parameters

| | |
|---------------------------------|--------------------------|
| Product family | System LM |
| Conductor connection system | Clamping yoke connection |
| Fitted to PCB | Soldered connection |
| Outgoing direction of conductor | 90° |
| Pitch | 5.08 mm |
| Pitch in inch | 0.2 inch |
| No. of poles | 12 |
| Fitted by customer | yes |
| Max. adjacent poles per row | 48 |
| No. of rows | 2 |
| Solder pin length | 3.5 mm |
| Dia. of fitting hole | 1.3 mm |
| Fitting hole tolerance | + 0.1 mm |
| No. of solder pins per pole | 1 |

System parameters

| | |
|-------------------------------------------|------------------------|
| Screwdriver blade | 0.6 x 3.5 |
| Screwdriver blade standard | DIN 5264 |
| Tightening torque, min. | 0.4 Nm |
| Tightening torque, max. | 0.5 Nm |
| Clamping screw | M 2.5 |
| Stripping length | 6 mm |
| L1 in mm | 25.4 mm |
| L1 in inch | 1 inch |
| Electric shock protection to DIN VDE 0470 | IP 20 |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

Material data

| | |
|-------------------------------|---------------------|
| Insulating material | Wemid (PA) |
| Colour | orange |
| colour chart | Similar to RAL 2000 |
| Insulating material group | I |
| Flammability class UL 94 | V-0 |
| CTI | >= 600 |
| Temperature of glow-wire test | 750 °C |
| Duration of glow-wire test | 30 S |
| Contact base material | Copper alloy |
| Contact surface | tinned |
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |

Connectable conductors

| | |
|---------------------------------------------------|------------------------|
| Clamping range, min. | 0.2 mm ² |
| Clamping range, max. | 2.5 mm ² |
| AWG, min. | 24 |
| AWG, max. | 14 |
| O.D. of conductor insulation, max. | 2.9 mm |
| Solid, min. H05(07) V-U | 0.2 mm ² |
| Solid, max. H05(07) V-U | 2.5 mm ² |
| Flexible, min. H05(07) V-K | 0.2 mm ² |
| Flexible, max. H05(07) V-K | 1.5 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, min. | 0.25 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, max. | 1.5 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.25 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 1.5 mm ² |
| Gauge to EN 60999 a x b; ø | 2.4 mm x 1.5 mm; 1.9mm |

DIN IEC rating data

| | |
|--------------------------------------------------------------|--------|
| Rated current, min. No. pins (Tu=20°C) | 17.5 A |
| Rated current, max. No. pins (Tu=20°C) | 16 A |
| Rated current, min. No. pins (Tu=40°C) | 17.5 A |
| Rated current, max. No. pins (Tu=40°C) | 14.2 A |
| Rated voltage for overvoltage class/pollution severity II/2 | 630 V |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V |

DIN IEC rating data

| | |
|--------------------------------------------------------------------------------|-------------------|
| Rated voltage for overvoltage class/pollution severity III/3 | 250 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 4 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV |
| Short-time withstand current resistance | 3 x 1s with 120 A |

CSA rating data

| | |
|------------------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor (field wiring), min. | 24 |
| AWG conductor (field wiring), max. | 14 |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor, min. | 24 |
| AWG conductor, max. | 14 |

Approvals

Approvals institutes



Downloads

| | |
|---------------------------------------|----------|
| CAD Library (P-CAD Format - Standard) | LM2H.lib |
|---------------------------------------|----------|

Classifications

| | |
|------------|----------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |
| eClass 4.1 | NK |
| eClass 5.0 | NK |
| eClass 5.1 | NK |

Similar products

| Order No. | Part designation | Version |
|-----------|------------------|---------|
|-----------|------------------|---------|

| | | |
|------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1769240000 | LM2H5.08/4 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 4, 90°, Box |
| 1769250000 | LM2H5.08/6 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 6, 90°, Box |
| 1769260000 | LM2H5.08/8 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 8, 90°, Box |
| 1769270000 | LM2H5.08/10 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 10, 90°, Box |
| 1769290000 | LM2H5.08/14 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 14, 90°, Box |
| 1769300000 | LM2H5.08/16 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 16, 90°, Box |
| 1769310000 | LM2H5.08/18 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 18, 90°, Box |
| 1769320000 | LM2H5.08/20 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 20, 90°, Box |
| 1769330000 | LM2H5.08/22 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 22, 90°, Box |
| 1769340000 | LM2H5.08/24 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 24, 90°, Box |
| 1769350000 | LM2H5.08/26 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 26, 90°, Box |
| 1769360000 | LM2H5.08/28 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 28, 90°, Box |
| 1769370000 | LM2H5.08/30 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 30, 90°, Box |
| 1769380000 | LM2H5.08/32 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 32, 90°, Box |
| 1769390000 | LM2H5.08/34 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 34, 90°, Box |
| 1769400000 | LM2H5.08/36 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 36, 90°, Box |
| 1769410000 | LM2H5.08/38 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 38, 90°, Box |

| | | |
|------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1769420000 | LM2H5.08/40 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 40, 90°, Box |
| 1769430000 | LM2H5.08/42 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 42, 90°, Box |
| 1769440000 | LM2H5.08/44 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 44, 90°, Box |
| 1769450000 | LM2H5.08/46 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 46, 90°, Box |
| 1769460000 | LM2H5.08/48 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, No. of poles: 48, 90°, Box |