

TM
TM 201/15 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com



Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

Type	TM 201/15 V0
Order No.	1798620000
Version	TM, Sleeve x 5 mm, PVC, Colour: Transparent, Conductor O.D.: 1.5 - 2.5 mm
GTIN (EAN)	4032248243358
Qty.	1,000 pc(s).

TM
TM 201/15 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	5 mm	Width (inches)	0.197 inch
Height	15 mm	Height (inches)	0.591 inch
Depth	5 mm	Depth (inches)	0.197 inch
Net weight	0.28 g		

General data

Colour	Transparent	Material	PVC
Operating temperature range	-40...80 °C	Recommended industries	Transportation, Machinery
Type of printing	blank	UL 94 flammability rating	V-0
Width	5 mm		

Conductor and cable markers

Conductor O.D.	1.5 - 2.5 mm	Conductor O.D., max.	2.5 mm
Conductor O.D., min.	1.5 mm	Conductor cross-section, max.	1.5 mm ²
Conductor cross-section, min.	0.25 mm ²		

Classifications

ETIM 3.0	EC001530	ETIM 4.0	EC001530
ETIM 5.0	EC001530	ETIM 6.0	EC001530
UNSPSC	44-12-17-08	eClass 5.1	27-14-91-03
eClass 6.2	27-14-91-29	eClass 7.1	27-14-91-29
eClass 8.1	27-14-91-03	eClass 9.0	27-14-07-08
eClass 9.1	27-40-04-01		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD, Zuken E3.S
------------------	--

TM
TM 201/15 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Accessories
Blank


TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.	
TM-I 15 MC NE SI	1609981697	TM-I, Insert markers, 15 x 4 mm, Silver	4008190137410400	400 pc(s).	
TM-I 15 MC NE VI	1427870000	TM-I, Insert markers, 15 x 4 mm, Violet	4050118231847400	400 pc(s).	
TM-I 15 MC NE BL	1609981693	TM-I, Insert markers, 15 x 4 mm, Blue	4008190367831400	400 pc(s).	
TM-I 15 MC NE GE	1609981687	TM-I, Insert markers, 15 x 4 mm, Yellow	4008190914776400	400 pc(s).	
TM-I 15 MC NE GN	1609981688	TM-I, Insert markers, 15 x 4 mm, Green	4008190398705400	400 pc(s).	
TM-I 15 MC NE RT	1609981686	TM-I, Insert markers, 15 x 4 mm, Red	4008190367824400	400 pc(s).	
TM-I 15 MC NE WS	1609981044	TM-I, Insert markers, 15 x 4 mm, White	4008190914783400	400 pc(s).	
Discontinued	2016-12-31T00:00:00+01:00	TM-I 15 MC NE GR	1427880000	TM-I, Insert markers, x 4 mm, Grey	4050118231854 400 pc(s).