

## RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 27 ... 26, with strain relief



### Ethernet

#### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	4.6 g
Custom tariff number	85366990
Country of origin	Taiwan

#### Technical data

##### Mechanical characteristics

Number of positions	8
Shielded	yes
Insertion/withdrawal cycles	≥ 750
Connection method	IDC connection technology
Conductor cross section	0.14 mm <sup>2</sup> ... 0.18 mm <sup>2</sup> (stranded)
Connection cross section AWG	27 ... 26 (stranded)
Cable exit	straight

##### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
---------------------------------	------------------

##### Material data

Flammability rating according to UL 94	V2
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel

# RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716

## Technical data

### Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
Rated current	0.5 A
Overvoltage category	I
Degree of pollution	2

### Standards and Regulations

Flammability rating according to UL 94	V2
--	----

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 7.0	27440309
eCl@ss 8.0	27440205
eCl@ss 9.0	27440205

### ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

## Approvals

### Approvals

---

## RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716

### Approvals

Approvals

EAC

---

Ex Approvals

---

Approvals submitted


---

### Approval details

EAC
-----

### Drawings

Dimensional drawing



RJ45 male insert

---