




The new caps for the Multimec switches 1SS / 1LS / 1IS is optimized with a "snap on" system to ensure the cap to stay on the switch actuator even under heavy vibrations or similar scenarios.

- The 1SS cap is a solid cap which can be supplied in different colours
- The 1LS cap is a solid cap like 1SS, but with a small round lens for intensive or smooth illumination
- The 1IS cap is a transparent or milk white cap like 1SS, for intensive or smooth illumination




Distributor:

### Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:  
LED: -40/+85°C  
solid cap +65°C  
transparent +85°C
- actuation force: 2.0, 3.5, 6.5 N




### Dimensions (through-hole) 1SS



### Dimensions (w. LED) 1LS



### Dimensions (SMD) 1IS



### HOW TO ORDER

<b>5 G</b>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Switch</b>	<b>Mounting</b>	<b>Actuation force</b>	<b>LED</b>	<b>Cap</b>	<b>Colour code</b>	<b>Lens</b>	<b>Height/1IS</b>
	<b>TH9</b> through-hole	<b>20</b>	<b>01</b> blue	<b>1IS</b> transparent	<b>00</b> blue	<b>1</b> transparent	<b>10.4</b>
	<b>SH9</b> surface mount	<b>35</b>	<b>22</b> green		<b>03</b> grey	<b>6</b> frosted white	<b>11.0</b>
		<b>65</b>	<b>42</b> yellow	<b>1LS</b> with lens	<b>08</b> red	<b>2</b> green	<b>12.0</b>
			<b>61</b> white		<b>09</b> black	<b>4</b> yellow	<b>15.0</b>
			<b>82</b> red		<b>11</b> transparent	<b>8</b> red	<b>Height/1LS</b>
			<b>2242</b> green/yellow		<b>16</b> frosted white		<b>12.0</b>
			<b>8222</b> red/green				<b>15.0</b>

### Switch to be used: 5E or 5G

<b>5 E</b>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>5 G</b>	<b>Mounting</b>	<b>Actuation force</b>	<b>Cap</b>	<b>Colour code</b>	<b>Height</b>
	<b>TH9</b> through-hole	<b>20</b>	<b>1SS</b> solid colour	<b>00</b> blue	<b>08.0</b>
	<b>SH9</b> surface mount	<b>35</b>		<b>02</b> green	<b>09.5</b>
		<b>65</b>		<b>03</b> grey	<b>10.4</b>
				<b>04</b> yellow	<b>11.0</b>
				<b>06</b> white	<b>12.0</b>
				<b>08</b> red	<b>15.0</b>
				<b>09</b> black	

Dimensions (mm) Unless otherwise specified, all tolerances  $\pm 0,2$

**Ordering example:** 5GTH93501+1LS03115.0

See colour codes on our website: [www.mec.dk](http://www.mec.dk)