

Coupling - VS-MP-PPC/CG-XL-PO/10G - 1403688

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Multi-port power and data connection: push/pull power and RJ45, 10 Gbps, for passive PROFINET cabling to robots, including mounting foot.

Product description

Push/pull power and data coupling; version 14



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 664370
Weight per Piece (excluding packing)	22.22 g
Custom tariff number	85366990
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Mechanical characteristics

Connection profile	Data/power: 8/5-pos.
Insertion/withdrawal cycles	> 1000 (Data) <= 100 (Power)
Connection method	Spring connection / IDC
Max. cable diameter	7 mm ... 10.5 mm (Data cable gland)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP65

Material data

Housing material	Aluminum press-drawn section / die-cast zinc
------------------	----------------------------------------------

Electrical characteristics

Nominal voltage U _N	24 V
--------------------------------	------

Coupling - VS-MP-PPC/CG-XL-PO/10G - 1403688

Technical data

Electrical characteristics

Nominal current I _N	16 A
Transmission characteristics (category)	CAT6 _A

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801

ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC001134
ETIM 5.0	EC001134

UNSPSC

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted


Approval details

EAC

Coupling - VS-MP-PPC/CG-XL-PO/10G - 1403688

Drawings

Drilling diagram



Dimensioned drawing

