

Panel mounting frames - CUC-V04-F-POBK-90 - 1407411

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Panel mounting frames, Degree of protection: IP65/67, Material: Plastic



Ethernet

Key commercial data

Packing unit	1 pc
GTIN	 4 046356 771801
Weight per Piece (excluding packing)	7.2 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Mechanical characteristics

Standards/specifications	IEC 61076-3-106
Locking type	Push Pull
Insertion/withdrawal cycles	≥ 750
Color	black

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65/IP67

Material data

Inflammability class according to UL 94	V0
Housing material	Plastic

Classifications

eCl@ss

eCl@ss 4.0	272607xx
------------	----------

Panel mounting frames - CUC-V04-F-POBK-90 - 1407411

Classifications

eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261207
eCl@ss 7.0	27440210

ETIM

ETIM 3.0	EC002310
ETIM 4.0	EC002310
ETIM 5.0	EC002310

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Accessories

Accessories

Female insert


RJ45 socket insert - CUC-V04-BU-90 - 1407408



RJ45 socket insert, 1-way, for PCB assembly, CAT5e, 8-pos., shielded, with angled solder pins (SMD)

Drawings

Dimensioned drawing



Panel mounting frame dimensional drawing

