






THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPERTY OF BEL/STEWART/TRP CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF TRP CONNECTOR.

PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING US PATENTS:
5736910 5939955 6425781 6428361 6554638 6840817 7123117
7429195 7717749 7808751 6217391 6149050 7924130

REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN
D		LOGO CHANGE	24APR2013	TY
E		COMPANY LOGO CHANGE AND EC-1409035	08JAN2015	TYR



8G18 GIGABIT CIRCUIT



1. MATERIALS:
- HOUSING: HIGH TEMPERATURE NYLON, BLACK, UL 94V-0
 - SHIELD: 0.20mm THICK, BRASS PREPLATED WITH 0.76 um MIN SEMI-BRIGHT NICKEL; POST-DIPPED WITH 2 um MIN SAC ALLOY LEAD FREE SOLDER
 - CONTACT TAILS: 0.25mm THICK, PHOSPHOR BRONZE, 1.27 um MIN OVERALL NICKEL UNDERPLATE, 3 um MIN TIN PLATE
 - MOD JACK CONTACTS: 0.25mm THICK, PHOSPHOR BRONZE, 1.27 um MIN OVERALL NICKEL UNDERPLATE, WITH 0.76um MIN LOCALIZED GOLD PLATE AT PLUG INTERFACE
 - LIGHT PIPE: POLYETHER SULFONE

2 RJ45 JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUB-PART F.

- 3 MAGNETICS:
- APPLICATION: 10/100/1000 BASE-T
 - IMPEDANCE: 100 OHMS
 - TURNS RATIO (CHIP:CABLE): 1:1 ALL FOUR PAIRS
 - OPEN CIRCUIT INDUCTANCE (OCL): 350uH MIN @100kHz, 0.1VRMS, 8mADC BIAS FROM 0°C TO 70°C, ALL FOUR PAIRS
 - ALL FOUR PAIRS BI-DIRECTINAL
 - PERFORMANCE @ 25°C:
 - INSERTION LOSS (IL): 1.1dB MAX FROM 0.5MHz TO 100MHz
 - RETURN LOSS (RL): 18dB MIN FROM 0.5MHz TO 40MHz
 - 12-20LOG(f/80)dB MIN FROM 40.1MHz TO 100MHz
 - CROSSTALK ATTENUATION: 35dB MIN FROM 0.5MHz TO 40MHz
 - 33-20LOG(f/50)dB MIN FROM 40.1MHz TO 100MHz
 - COMMON MODE REJECTION RATIO (CMRR): 30dB MIN FROM 0.5MHz TO 100MHz
 - ISOLATION VOLTAGE:2250VDC (MAX) FOR 60 SECONDS WITH A RISE TIME OF 500V/SEC

4 OPERATING TEMPERATURE: FROM 0°C TO 70°C

5 LIGHT PIPES ARE USED TO TRANSMIT LIGHT OF SMD LED'S MOUNTED ON CUSTOMER BOARD.



6 ALL DIMENSIONS ARE NOMINAL UNLESS OTHERWISE NOTED.





7 TRP CONNECTOR LOGO,PART NUMBER, DATE CODE, COUNTRY OF ORIGIN, AND AGENCY APPROVAL MARKING IN APPROXIMATE LOCATION SHOWN



8 PART SHOULD BE COMPLIANT TO WAVE SOLDERING PROCESS ONLY, PREHEAT TEMPERATURE IS 120°C TO 160°C, 120 SECONDS TO 180 SECONDS, PEAK SOLDERING TEMPERATURE IS 260°C MAX, 10 SECONDS MAX.

9 PART SHOULD BE COMPLIANT TO BOTH WAVE SOLDERING PROCESS, PREHEAT TEMPERATURE IS 120°C TO 160°C, 120 SECONDS TO 180 SECONDS, PEAK SOLDERING TEMPERATURE IS 260°C MAX, 10 SECONDS MAX, AND IR REFLOW SOLDERING PROCESS, PEAK SOLDERING TEMPERATURE 260°C MAX, DURATION TIME 10 SECONDS MAX, OVER 230°C WITHIN 40-60 SECONDS.

WAVE 8	WITH TRAY	1840882-2
BOTH 9	WITH REEL	1840882-1
SOLDER PROCESS	PACKAGE	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ROY LIU/COLIN ZHU 17NOV2010	 trp CONNECTOR a bel group DONGGUAN CHINA	
DIMENSIONS: mm		CHK TOWER YU 17NOV2010		
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD KEITH ZHU 17NOV2010	
	0 PLC ±0.25 1 PLC ±0.25 2 PLC ±0.25 3 PLC ±0.25 4 PLC ±0.25 ANGLES ±° APPLICATION SPEC ±°		MODEL NAME MAGJACK	
	-		DESC IX1 8G18 GIGABIT TAB DOWN LOW PROFILE NO LED W/ LIGHT PIPE	
	PRODUCT SPEC 108-2207		SIZE A1	
-		CAGE CODE C=1840882		RESTRICTED TO -
CUSTOMER DRAWING		SCALE 5:1		
		SHEET 1 OF 2		
		REV E		



THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN ROY LIU/COLIN ZHOU 17NOV2010	 trp CONNECTOR a bel group		DONGGUAN CHINA	
DIMENSIONS:		CHK TOWER YU 17NOV2010				
mm		APVD KEITH ZHU 17NOV2010				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		MODEL NAME	DESC			
		MAGJACK	IX1 8G18 GIGABIT TAB DOWN LOW PROFILE NO LED W/ LIGHT PIPE			
		SINGLE NON-POE	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
			A1		C=1840882	-
			CUSTOMER DRAWING			
			SCALE	SHEET	REV	
PRODUCT SPEC	APPLICATION SPEC	108-2207				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bel:

1840882-2