



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

04 MTE RCPT HSG SR LATCH .100

[AMPMODU](#) | [AMPMODU MTE](#)

104920-3

TE Internal Number: 104920-3

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **4**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [.1 in]**

Color **Black**

Product Drawings

[RECEPTACLE HOUSING, AMPMODU MTE, SINGLE ROW, .100 CL , POLARIZED WITH LATCH](#)

PDF (**TIFF AVAILABLE**)
English

[RECEPTACLE HOUSING, AMPMODU MTE, SINGLE ROW, .100 CL , POLARIZED WITH LATCH](#)

PDF (**TIFF AVAILABLE**)
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Type	Housing
	Applies To	Wire/Cable
	Connector Style	Receptacle
	Strain Relief	Without
	Product Type	Connector
Configuration Features	Number of Positions	4
	Number of Rows	1
Electrical Characteristics	Dielectric Withstanding Voltage	600 VAC
	Operating Voltage	267 V
	Insulation Resistance (MΩ)	5000
Body Features	Color	Black
Contact Features	Contact Type	Socket
	Contact Base Material	Copper Alloy
	Contact Layout	Inline
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	Without
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Latch
	Mating Alignment	With
	Mating Alignment Type	Latch
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Configuration	Both Ends Closed
	Housing Color	Black
	Housing Material	Polycarbonate GF
Dimensions	Length (mm)	10.1

Dimensions	Length (mm)	10.1
	Height (in)	.2
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Header
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1
	Packaging Method	Package
Other	Comment	Refer to AMPMODU contacts for crimp snap-in replacement receptacle or pin contacts.
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	