






.025 (0.64) Series Connectors

Wire to Wire Applications

.025 (0.64) Receptacle Contact (for Contact Lance)

Contact	Applicable Wire	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool Part No.
				S.T.	L.P.	
 .025(0.64) Receptacle, crimping type Application specification: 114-5250	0.22-0.5mm ²	0.95-1.7mm	Copper alloy/Pre-tinned	1123343-1	1318143-1	1463260-1 Instruction Sheet 411-5981
			Copper alloy/Sel. Gold	1123343-2	1318143-2	
 .025(0.64) Receptacle, IDC type Application specification: 114-5276	0.3-0.5mm ²	1.1-1.35mm	Copper alloy/Post-tinned	1318688-1	—	—
 .025(0.64) Receptacle, IDC type Application specification: 114-5276	0.08-0.14mm ²	1.1-1.4mm	Copper alloy/Post-tinned	1565403-1	—	—
	0.22mm ²	0.8-1.2mm	Copper alloy/Post-tinned	1565404-1	—	—

.025(0.64 III) Receptacle Contact (for Housing Lance)

Contact	Applicable Wire	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool Part No.
				S.T.	L.P.	
 .025(0.64 III) Receptacle, crimping type Application specification: 114-5329	0.13-0.22mm ²	0.81-1.05mm	Copper alloy/Pre-tinned	1674936-1	1827805-1	1762338-1 Instruction Sheet 411-78188
			Copper alloy/Sel. Gold	1674936-2	1827805-2	
 .025(0.64 III) Receptacle, crimping type Application specification: 114-5329	0.35-0.56mm ²	1.06-1.7mm	Copper alloy/Pre-tinned	1674311-1	1827804-1	1762337-1 Instruction Sheet 411-78187
			Copper alloy/Sel. Gold	1674311-2	1827804-2	

* Contacts Receptacles for Conn. 1473672-1

5

Wire to Wire Connectors