



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

16 MOD IV HSG COMP W/LATCH POL

[AMPMODU](#) | [AMPMODU IV/V](#)

104422-1

TE Internal Number: 104422-1

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **16**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**

Mating Retention **With**

Product Drawings

[HOUSING, MOD IV, DBL ROW, .100 X .100 C/L, WITH POLARIZATION & LATCH](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing

2.54 mm [.1 in]

Glow Wire Rating

Standard Part - Not Glow Wire

Connector Type

Housing









Applies To

Wire/Cable

	Connector Style	Receptacle
	Strain Relief	With
	Product Type	Connector
Configuration Features	Number of Positions	16
	Number of Rows	2
Electrical Characteristics	Dielectric Withstanding Voltage	750 VAC
	Operating Voltage	267 V
	Insulation Resistance (MΩ)	5000
Contact Features	Contact Type	Socket
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Retention	With
	PCB Mount Retention	Without
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Alignment	With
	Mating Alignment Type	Latch
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Configuration	Both Ends Closed
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Height	8.51 mm [.335 in]
	Length	20.32 mm [.8 in]
Usage Conditions	Flame Retardant	Yes
Operation/Application	For Use With	Pin Header
Packaging Features	Packaging Quantity	500
	Packaging Method	Bag

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR CONTACTS	WIRE-TO-BOARD CONNECTOR HOUSINGS	WIRE-TO-BOARD CONNECTOR CONTACTS	SMA CONNECTORS
<p>MOD IV RECP LP 1-102316-3</p>	<p>20 MOD IV HSG COMP W/LATCH POL 104422-2</p>	<p>MOD V RECP LP 1-87309-3</p>	<p>QMA 4 HOLE FLANGE MT JACK - ST 1408341-1</p>
<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>