

REEL DIA. REF.

FEED DIRECTION

.500 [12.7] DIA. HOLE THRU

$\pm .005 [\pm 0.13]$ PITCH

$\pm .005 [\pm 0.13]$

.157 [4.0]

$\pm .005 [\pm 0.13]$

.059 [1.5] DIA. HOLE (TYP.)

.079 [2.0]

.787 [20.0]

.216 [5.5] REF.

WIDTH

$\pm .005 [\pm 0.13]$

FEED DIRECTION

.016 [0.4] REF.

WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

TAPE AND REEL SPECIFICATIONS:

1. TAPE:
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
1.732 [44.0] WIDE; 0.788 [20] PITCH
2. REEL:
13.0 [330.2] DIA. 500 PIECES OF
PART NO. 1058 PER REEL.

12.16.14	CHANGE AS PER ECN 14-125	A
DATE	DESCRIPTION	REV.

KEYSTONE ELECTRONICS CORP. www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME 2032mm SM COIN CELL HOLDER ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 5.16.13
		APP'D LN	SCALE 1X
TOLERANCES INCH [MM] DECIMAL $\pm .015$ [± 0.38] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE C	DWG NO. 1058TR	