



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

03 MTE RCPT HSG SR LATCH .100

AMPMODU | AMPMODU MTE

104920-2

TE Internal Number: 104920-2

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **3**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [.1 in]**

Color **Black**

Product Drawings

RECEPTACLE HOUSING, AMPMODU MTE, SINGLE ROW, .100 CL , POLARIZED WITH LATCH

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

3D PDF

PDF
English

Catalog Pages/Data Sheets

AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0

PDF
English

Product Specifications

Application Specification

AMPMODU MTE Interconnection System

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing

2.54 mm [.1 in]

Connector Type

Housing

	Applies To	Wire/Cable
	Connector Style	Receptacle
	Strain Relief	Without
	Product Type	Connector
<hr/>		
Configuration Features	Number of Positions	3
	Number of Rows	1
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	600 VAC
	Operating Voltage	267 V
	Insulation Resistance (MΩ)	5000
<hr/>		
Body Features	Color	Black
<hr/>		
Contact Features	Contact Type	Socket
	Contact Base Material	Copper Alloy
	Contact Layout	Inline
<hr/>		
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
<hr/>		
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	Without
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Latch
	Mating Alignment	With
	Mating Alignment Type	Latch
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Configuration	Both Ends Closed
	Housing Color	Black
	Housing Material	Polycarbonate GF
<hr/>		
Dimensions	Length (mm)	7.56
	Height (in)	.2
<hr/>		

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Header
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1
	Packaging Method	Package
Other	Comment	Refer to AMPMODU contacts for crimp snap-in replacement receptacle or pin contacts.

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)