

4805 (3/11)

					\bigcirc \uparrow \checkmark			
THIS DRAWING IS A CO	ONTROLLED DOCUMENT.	DWN 24JAN95 R. VESTAL CHK 24JAN95		TE Connectivity				ý
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	R. SWING apvd 24jan95	NAME					
mm		D. SELF			PLI	JG.		
	0 PLC ± - 1 PLC ± - 2 PLC ± 0.13 3 PLC ± -	PRODUCT SPEC	_	UNIVERS	2 CIR		(TM)	
T .	4 PLC ± – ANGLES ± 0°30'	_	SIZE	CAGE CODE DRAWING N				RESTRICTED TO
MATERIAL NYLON,	FINISH _	WEIGHT]A 1	00779 C- 35	50777			_
		CUSTOMER DRAWING			SCALE	4:1	0F 1	1 ^{REV} AD

		2					1			
_	LOC	DIST				REVISIONS				
	СМ	0	P	LTR		DESCRIPTION		DATE	DWN	APVD
•				AD	REVISED PER ECR-	-17-006277		24MAY2017	BW	KR

1 MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOKTM CAP OR HEADER.

2 SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS [1.0] LBS. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS [.5] LBS.

3 DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

4 FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, NO RIBS OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.

NOT MANUFACTURED IN U.S.

4 UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE ON ANY SIDE OF HOUSING.

 $\sqrt{7}$ position #1 locator feature may be round or oblong (as depicted).

8 TRADEMARK LOCATION (AMP OR TE CONNECTIVITY) SHOWN FOR CONVENIENCE, LOGO MAY BE ON ANY EXTERNAL SURFACE.

MANUFACTURING LOCATION ID (OPTIONAL).

BLACK	1-350777-9
GRAY	1-350777-8
BLUE	1-350777-6
GREEN	1-350777-5
YELLOW	1-350777-4
ORANGE	1-350777-3
RED	1-350777-2
BROWN	1-350777-1
5	350777-4
NATURAL	350777-1
COLOR	PART NUMBER
E TE	TE Connectivity

R

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-350777-4</u>