



Active

PRODUCT DRAWING
English

TE CONNECTIVITY (TE)

26 MODIV HSG COMP DR .100 EARS

AMPMODU | AMPMODU IV/V

1-86264-7

TE Internal Number: 1-86264-7

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **26**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**

Product Drawings

[CONNECTOR, MOD IV, CRIMP SNAP-IN, DOUBLE ROW, .100X.100 CENTERS](#)

PDF (TIFF AVAILABLE)

English

[CONNECTOR, MOD IV, CRIMP SNAP-IN, DOUBLE ROW, .100X.100 CENTERS](#)

PDF (TIFF AVAILABLE)

English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

| | |
|--------------------|--------------------------------------|
| Row-to-Row Spacing | 2.54 mm [.1 in] |
| Connector Style | Receptacle |
| Glow Wire Rating | Standard Part - Not Glow Wire |
| Strain Relief | Without |
| Connector Type | Housing |
| Product Type | Connector |

Configuration Features

| | |
|---------------------|-----------|
| Number of Positions | 26 |
| Number of Rows | 2 |

Electrical Characteristics

| | |
|-------------------|----------------|
| Operating Voltage | 250 VAC |
|-------------------|----------------|

| | | |
|-----------------------|----------------------------------|----------------------------|
| Contact Features | Contact Current Rating (A) | 3 |
| | Contact Type | Socket |
| | Contact Base Material | Beryllium Copper |
| Termination Features | Termination Method to Wire/Cable | Crimp |
| Mechanical Attachment | Mating Connector Lock | Without |
| | Mating Alignment | Without |
| Housing Features | Centerline | 2.54 mm [.1 in] |
| | Housing Material | Nylon - GF |
| | Housing Configuration | Both Ends Closed |
| | Housing Color | Black |
| Dimensions | Length | 45.72 mm [1.8 in] |
| | Height | 6.1 mm [.24 in] |
| Usage Conditions | Operating Temperature Range (°C) | -65 – 105 |
| Industry Standards | UL Flammability Rating | UL 94V-0 |
| Packaging Features | Packaging Quantity | 1 |
| | Packaging Method | Package |

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)