



✓ Active

↓ **PRODUCT DRAWING**  
English

TE CONNECTIVITY (TE)

32 MODIV HSG DR MRKD .100 EARS

[AMPMODU](#) | [AMPMODU IV/V](#)

104855-4

TE Internal Number: 104855-4

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Number of Positions **32**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [ .1 in ]**

Color **Black**

Product Drawings

[HSG, PLZ WITH MTG EARS, DBL ROW, 2.54\[.100\]X2.54\[.100\] C/L MOD IV](#)

PDF (**TIFF AVAILABLE**)  
English

[HSG, PLZ WITH MTG EARS, DBL ROW, 2.54\[.100\]X2.54\[.100\] C/L MOD IV](#)

PDF (**TIFF AVAILABLE**)  
English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF  
English

Application Specification

[AMPMODU MOD IV, IV1/2, And V Receptacles And Housings](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
Connector Style	<b>Receptacle</b>
Strain Relief	<b>Without</b>
Connector Type	<b>Housing</b>
Product Type	<b>Connector</b>
Applies To	<b>Wire/Cable</b>

Configuration Features

Number of Positions	<b>32</b>
Number of Rows	<b>2</b>

Electrical Characteristics	Operating Voltage	<b>250 VAC</b>
Body Features	Color	<b>Black</b>
Contact Features	Contact Type	<b>Socket</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp</b>
Mechanical Attachment	Mating Retention	<b>Without</b>
	PCB Mount Retention	<b>Without</b>
	Mating Connector Lock	<b>Without</b>
	Mating Alignment	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment Type	<b>Polarization</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Material	<b>Thermoplastic</b>
	Housing Configuration	<b>Both Ends Closed</b>
	Housing Color	<b>Black</b>
Dimensions	Length (mm)	<b>59.94</b>
	Height (mm)	<b>6.1</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
Operation/Application	For Use With	<b>Contact</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Quantity	<b>1</b>
	Packaging Method	<b>Package</b>
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	