



FEATURES:

- Pomona's Model 1756 is part of a family of test accessories ideal for low voltage precision measurements.
- Spade lugs are of high conductivity, gold plated ETP copper alloy 110, to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF).
- Thermal EMF is generated at the junction of dissimilar metals at different temperatures and is a common source of error in low micro and nano volt measurements.
- In addition, low Thermal EMF spade lugs are attached to the wire shield to lessen interference, interaction, or leakage which might affect the accuracy of your precision voltage measurement.

MATERIALS:

Spade Lugs: ETP (Electrolytic Tough Pitch) 110 Copper Alloy, 1/2 Hard, Gold Plated

Insulation: Polypropylene, molded to spade lug body and wire. Color: Red and Black

Marking: "POMONA ELECTRONICS CALIF"

Cable: 12 AWG; Stranding 7 x 38/36 Bare Copper, Braided Bare Copper Shield, Inner Insulation: Natural

Polyethylene, O.D. .144" (3,66mm), Outer Jacket: PVC, Color: Black, O.D. .246" (6,25mm),

Marking: "POMONA 1756-XX"

Shield Lead: 18 AWG, Stranding 65 x 36 t.c., PVC Insulated, O.D.: .144" (3,66)

RATINGS:

Operating Voltage: 2000 VRMS/DC

Operating Temperature: +55° C (+131°F). Max.

Current: 20 Amperes Max.

ORDERING INFORMATION: Model 1756-XX

XX = Length in inches, Standard lengths: 24" (60,96cm) & 48" (121,92cm).

Additional lengths can be quoted upon request.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[1756-24](#) [1756-48](#)