

**SACC-V-3CON-PG7/CI**

Order No.: 1527964

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1527964>Valve connector, 3-pos., type CI, unconnected, screw connection,  
cable screw connection Pg7**Commercial data**

GTIN (EAN)	
sales group	D123
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 79 (PC-2005)

**Product notes**WEEE/RoHS-compliant since:  
02/21/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General data**

Rated current at 40°C	6 A
Rated voltage	250 V
Number of positions	3


Volume resistance	≤ 15 mΩ
Insulation resistance	≥ 100 MΩ
Ambient temperature (operation)	-40 °C ... 125 °C (valve plug)

#### General characteristics

Surge voltage category	II
Pollution degree	3
Degree of protection	IP65
Contact material	CuZn
Contact surface material	Ni
Valve plug contact insert material	PA6
Material, housing, valve plug	PA6
Sealing material	NBR
Connection method	Screw connection
Conductor cross section stranded min.	0.34 mm <sup>2</sup>
Conductor cross section stranded max.	1.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	22
Conductor cross section AWG/kcmil max	16
External cable diameter	6 mm ... 8 mm
Status display	No

#### Diagrams/Drawings

##### Circuit diagram



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;