



CONNECTORS

## HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

### 16P MTA100 CONN ASSY 22AWG RED

MTA | MTA-100

1-640440-6

TE Internal Number: 1-640440-6

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Centerline **2.54 mm [ .1 in ]**

Number of Positions **16**

Number of Rows **1**

Contact Mating Area Plating Material **Tin-Lead**

Contact Mating Area Plating Material Finish **Bright**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**



#### Product Drawings

[MTA 100 CONNECTOR ASSEMBLY, 22 AWG, STANDARD](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

#### Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)

PDF  
English

#### Product Specifications

---

## Product Environmental Compliance

TE Material Declaration

[MD\\_1-640440-6\\_07162014422\\_dmtec](#)PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	<b>Connector</b>
	Connector Type	<b>Connector Assembly</b>
	Connector System	<b>Wire-to-Post</b>
	Wire/Cable Type	<b>Discrete Wire, Stranded</b>
	Strain Relief	<b>With</b>
	Sealed	<b>No</b>
	Connector Style	<b>Receptacle</b>
	Applies To	<b>Wire/Cable</b>
Connector Design	<b>Closed End</b>	
Configuration Features	Number of Positions	<b>16</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
Body Features	Cable Exit Angle	<b>90°</b>
Contact Features	Contact Mating Area Plating Material	<b>Tin-Lead</b>
	Contact Mating Area Plating Material Finish	<b>Bright</b>
	Contact Mating Area Plating Thickness	<b>2.03 µm [ 80 µin ]</b>
	Contact Termination Area Plating Thickness	<b>2.03 – 5.08 µm [ 80 – 200 µin ]</b>
	Contact Termination Area Plating Material	<b>Tin-Lead</b>
	Contact Type	<b>Socket</b>
	Contact Current Rating (A)	<b>5</b>
	Contact Layout	<b>Inline</b>
	Contact Termination Area Plating Material Finish	<b>Bright</b>
	Contact Base Material	<b>Copper Alloy</b>

Contact Base Material

Copper Alloy

Termination Features	Termination Method to Wire/Cable	<b>IDC</b>
Mechanical Attachment	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>Without</b>
	Contact Retention	<b>With</b>
	Contact Retention Type	<b>Locking Lance</b>
	Mating Retention Type	<b>Locking Ramp</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>Without</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Red</b>
	Housing Style	<b>Standard</b>
	Housing Material	<b>Nylon</b>
Dimensions	Height	<b>6.99 mm [ .275 in ]</b>
	Wire/Cable Size (AWG)	<b>22</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.3 – .4</b>
	Insulation Diameter	<b>1.52 mm [ .06 in ]</b>
	Length	<b>40.64 mm [ 1.6 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Operation/Application	For Use With	<b>MTA .100 Headers &amp; MTA .100 IDC Posted Connectors</b>
	Pick and Place Cover	<b>Without</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-2</b>
	UL File Number	<b>E28476</b>
	CSA Rating	<b>Certified</b>
	Agency/Standard	<b>CSA, UL</b>
	CSA File Number	<b>LR7189</b>
	UL Rating	<b>Recognized</b>
Packaging Features	Packaging Method	<b>Bag/Box</b>

---

Other

Comment

**Stripe may run down between ribs**

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

