



## HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### 08 MTE HDR SRRA LATCH W/HLDWN

[AMPMODU](#) | [AMPMODU MTE](#)

103904-7

TE Internal Number: 103904-7

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Centerline **2.54 mm [ .1 in ]**

Number of Positions **8**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Through Hole**

Number of Rows **1**

#### Product Drawings

[HEADER ASSY, AMPMODU MTE, RIGHT ANGLE, SINGLE ROW, .100CL .025 SQ POSTS, WITH LATCH & HOLD DOWNS](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

3D\_IJS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

#### Catalog Pages/Data Sheets

[AMPMODU\\_MTE\\_INTERCONNECT\\_SYSTEM\\_QRG\\_4-1773458-0](#)

PDF  
English

#### Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF  
English

#### Instruction Sheets

Instruction Sheet (U.S.)

[AMPMODU MTE CONNECTORS](#)

PDF  
English

Product Type Features	PCB Mounting Orientation	<b>Right Angle</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Connector Style	<b>Plug</b>
	PCB Orientation Feature	<b>No</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>8</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>
Electrical Characteristics	Dielectric Withstanding Voltage	<b>600 V</b>
	Insulation Resistance	<b>5000 M<math>\Omega</math></b>
	Termination Resistance	<b>15 M<math>\Omega</math></b>
Body Features	Header Type	<b>Shrouded</b>
Contact Features	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness ( $\mu\text{in}$ )	<b>30</b>
	Contact Termination Area Plating Thickness	<b>2.54 <math>\mu\text{m}</math> [ 100 <math>\mu\text{in}</math> ]</b>
	Contact Shape	<b>Square</b>
	Contact Termination Area Plating Material	<b>Tin-Lead</b>
	Tail Plating Material	<b>Tin-Lead</b>
	Tail Plating Thickness	<b>2.54 <math>\mu\text{m}</math> [ 100 – 200 <math>\mu\text{in}</math> ]</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Termination Area Plating Material Finish	<b>Matte</b>
	Contact Base Material	<b>Brass</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp, Insulation Displacement Crimp (IDC)</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>

	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Hold-Down</b>
	Contact Retention	<b>With</b>
	Mating Alignment Type	<b>Latched</b>
	Contact Retention Type	<b>Locking Lance</b>
	Mating Retention Type	<b>Hold-Down</b>
	Mating Alignment	<b>With</b>

---

Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>

---

Dimensions	Tail Length	<b>3.3 mm [ .13 in ]</b>
	Mating Post Length	<b>5.84 mm [ .23 in ]</b>
	PCB Thickness (Recommended)	<b>1.574 mm [ .062 in ]</b>
	Height	<b>13.59 mm [ .535 in ]</b>
	Length	<b>22.86 mm [ .9 in ]</b>

---

Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
------------------	----------------------------------	------------------

---

Operation/Application	For Use With	<b>Receptacle Housing Assembly</b>
	Pick and Place Cover	<b>Without</b>

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>





---

Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>23</b>

---

Other	Comment	<b>Use Keying Tool No. 91417-1 to remove post for keying.</b>
-------	---------	---

## CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD HEADERS & RECEPTACLES		WIRE-TO-BOARD HEADERS & RECEPTACLES	WIRE-TO-BOARD CONNECTOR HOUSINGS
			
<b>16 MTE HDR SRRA LTCH.100CL LF</b> 6-103635-5	<b>RP 1J 0.166W 9K53 0.1% 25PPM 1K RL</b> 9-2176088-8	<b>6 MTE HDR SRRA LATCH W/HLDWN</b> 5-103904-5	<b>4X4 MTE SHRD PIN SR POL .100CL</b> 5-103946-3
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS		
	<p>Connectors - FFC Connectors FFC   FFC</p> <p><b>008 HOUSING FFC RCPT 100CL SR - 487526-7</b></p> <p>TE INTERNAL NUMBER: 487526-7</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Connector Type <b>Housing</b></p> <p>Connector Style <b>Receptacle</b></p> <p>Centerline <b>2.54 mm</b></p> <p>Number of Positions <b>8</b></p> <p>Number of Rows <b>1</b></p>