



## HEADERS & RECEPTACLES



### TE CONNECTIVITY (TE) 08 MTE HDR SRRA LATCH W/HLDWN [AMPMODU](#) | [AMPMODU MTE](#)

103672-7  
TE Internal Number: 103672-7

Not EU RoHS or ELV Compliant  
[Find Compliant Alternatives](#)

Centerline **2.54 mm [ .1 in ]**

Number of Positions **8**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Through Hole**

Number of Rows **1**

✓ Active

[↓](#) **PRODUCT DRAWING**  
English

[↓](#) **3D PDF**

#### Product Drawings

[HDR ASSY, RTANG, SINGLE ROW 2.54\[.100\] CL, 0.64\[.025\] SQ POST, WITH PLZN HOLD DOWNS, AMPMODU MTE](#)

PDF  
English

#### CAD Files

[3D PDF](#)  
PDF  
3D

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[AMPMODU\\_MTE\\_INTERCONNECT\\_SYSTEM\\_ORG\\_4-1773458-0](#)  
PDF  
English

#### Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)  
PDF  
English

#### Instruction Sheets

Instruction Sheet (U.S.)

[AMPMODU MTE CONNECTORS](#)  
PDF  
English

Product Type Features	PCB Mounting Orientation	<b>Right Angle</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Connector Style	<b>Plug</b>
	PCB Orientation Feature	<b>No</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>8</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>
Electrical Characteristics	Dielectric Withstanding Voltage	<b>600 V</b>
	Insulation Resistance	<b>5000 M<math>\Omega</math></b>
	Termination Resistance	<b>15 M<math>\Omega</math></b>
Body Features	Header Type	<b>Shrouded</b>
Contact Features	Contact Mating Area Plating Material	<b>Tin-Lead</b>
	Contact Mating Area Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Termination Area Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Shape	<b>Square</b>
	Contact Termination Area Plating Material	<b>Tin-Lead</b>
	Tail Plating Material	<b>Tin-Lead</b>
	Tail Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Termination Area Plating Material Finish	<b>Bright</b>
	Contact Base Material	<b>Brass</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp, Insulation Displacement Crimp (IDC)</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>

	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Hold-Down</b>
	Contact Retention	<b>With</b>
	Mating Alignment Type	<b>Latched</b>
	Contact Retention Type	<b>Locking Lance</b>
	Mating Retention Type	<b>Hold-Down</b>
	Mating Alignment	<b>With</b>

---

Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>

---

Dimensions	Tail Length	<b>3.3 mm [ .13 in ]</b>
	Mating Post Length	<b>5.84 mm [ .23 in ]</b>
	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Height	<b>13.59 mm [ .535 in ]</b>
	Length	<b>22.86 mm [ .9 in ]</b>

---

Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
------------------	----------------------------------	------------------

---

Operation/Application	For Use With	<b>Receptacle Housing Assembly</b>
	Pick and Place Cover	<b>Without</b>

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>

---

Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>23</b>

---

Other	Comment	<b>Use Keying Tool No. 91417-1 to remove post for keying.</b>
-------	---------	---

---

Product Compliance [Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 1 Results

[View All](#)

Compare 0/10



Relation Type



RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - FFC Connectors  
FFC | FFC

## 008 HOUSING FFC RCPT 100CL SR - 487526-7

TE INTERNAL NUMBER: 487526-7

✓ Active

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **8**

Number of Rows **1**