



## STANDARD RECTANGULAR CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### MICRO MNL HDR ASSY SINGLE ROW

MATE-N-LOK | [Micro MATE-N-LOK](#)

1445093-9

TE Internal Number: 1445093-9

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Polarization**

Mating Retention **With**

Mating Retention Type **Locking Tab**

#### Product Drawings

[VERTICAL THRU HOLE HEADER ASSY, 0.76 MIC GOLD CONTACTS, W/PCB PLZN FEATURE,SGL R](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[SOFT\\_SHELL\\_PIN\\_AND\\_SOCKET\\_CONNECTORS\\_CATALOG](#)

PDF  
English

[1773458-4\\_MICRO\\_MATE\\_N\\_LOK\\_CONNECTOR\\_SYSTEM\\_QRG](#)

PDF  
English

#### Product Specifications

Application Specification

[Micro MATE-N-LOK Connectors](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	<b>Connector</b>
	PCB Mounting Orientation	<b>Vertical</b>
	Sealed	<b>No</b>
	Connector System	<b>Wire-to-Board</b>
	Connector Style	<b>Plug</b>
	Connector Type	<b>Header</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>9</b>
	Number of Rows	<b>1</b>
Electrical Characteristics	Operating Voltage	<b>250 VAC [ 250 VDC ]</b>
Body Features	Sealable	<b>No</b>
Contact Features	Contact Current Rating (A)	<b>5</b>
	Tail Plating Thickness	<b>2.54 <math>\mu\text{m}</math> [ 100 <math>\mu\text{in}</math> ]</b>
	Multiple Contact Types	<b>Without</b>
	Contact Type	<b>Pin</b>
	Tail Plating Material	<b>Tin-Lead</b>
	Contact Layout	<b>Inline</b>
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Method to Wire/Cable	<b>Solder</b>
Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Locking Tab</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Retention Bump</b>
	PCB Mount Alignment	<b>With</b>
	PCB Mount Alignment Type	<b>Polarization</b>
	Panel Mount Retention	<b>Without</b>
Housing Features	Centerline	<b>3 mm [ .118 in ]</b>
	Housing Material	<b>High Temperature Nylon</b>

Housing Color **Black**

Dimensions	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Tail Length	<b>3.18 mm [ .125 in ]</b>
	Insulation Diameter (Max) (mm)	<b>1.52</b>
	Wire/Cable Size (AWG)	<b>30 – 20</b>

Usage Conditions Operating Temperature Range **-40 – 105 °C [ -40 – 221 °F ]**

Operation/Application For Use With **Plug Housing**

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA File Number	<b>LR7189</b>
	VDE Tested	<b>Yes</b>
	CSA Rating	<b>Certified</b>
	UL Rating	<b>Recognized</b>
	Agency/Standard	<b>CSA, UL</b>
	UL File Number	<b>E28476</b>

Packaging Features	Packaging Quantity	<b>112</b>
	Packaging Method	<b>Tray, Tray/Box</b>

Product Compliance [Statement of Compliance PDF](#)  
[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors  
MATE-N-LOK | Micro MATE-N-LOK

**MICRO MNL RFECEPT**

Always EU RoHS/ELV Compliant





## HSG SINGLE R - 1445022-9

TE INTERNAL NUMBER: 1445022-9

✓ Active