

## Base strip - CIOC 4-1-LIH - 1701362

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Header, Nominal current: 5 A, Number of positions: 4, Pitch: 2.54 mm, Color: black, Contact surface: Gold, Mounting: Soldering

### Why buy this product

- Gold-plated contact system
- The CIOC 4-18-LI plug can be combined with -LIH or -LIV base strips for a horizontal or vertical PCB connection
- The CIOC plug-in plug range is complemented by a 4-pos. link plug with 2.54 mm pitch
- A plug-in tap at any point in the bus and power cable can be achieved using two CIOC 4-18-LI plugs



### Key commercial data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 046356 030472
Weight per Piece (excluding packing)	7.69 g
Custom tariff number	85366990
Country of origin	Japan
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Pitch	2.54 mm
Dimension a	7.5 mm
Pin spacing	2.54 mm

#### General

Range of articles	CIOC-LINK
Rated voltage (III/3)	160 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	5 A
Maximum load current	5 A

# Base strip - CIOC 4-1-LIH - 1701362

## Technical data

### General

Insulating material	PBT
Inflammability class according to UL 94	V0
Color	black
Number of positions	4

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440309

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

# Base strip - CIOC 4-1-LIH - 1701362

## Approvals

### Approval details

UL Recognized	
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	160 V


cUL Recognized	
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	160 V

EAC
-----

cULus Recognized
------------------

## Drawings

Drilling diagram



Dimensioned drawing

