

Pneumatic crimping tool - ZAP 40 - 1212630

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Pneumatic crimping pliers, for ferrules according to DIN 46228-1: 1992-08 and DIN 46228-4: 1990-09, for conductor cross section 0.25 - 4 mm², trapezoid crimping, lateral entry



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 661027

Technical data

Dimensions

Length (b)	190 mm
------------	--------

General

Compression	trapezoidal
Min. AWG, flexible, multi-strand	12
AWG max., flexible, multi-strand	2
Pressure range	4 bar ... 6 bar
Air consumption per compression	0.2 l

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	17130101
eCl@ss 7.0	17130101

Pneumatic crimping tool - ZAP 40 - 1212630

Classifications

eCl@ss

eCl@ss 8.0	21049090
------------	----------

ETIM

ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>