

CRIMPFOX-M RCI 6/DIE


Order No.: 1212073



<http://eshop.phoenixcontact.net/phoenix/treeViewClick.do?UID=1212073>

Die, for Crimpfox-M, for insulated cable lugs 0.1 - 0.4 mm² and 4 - 6 mm² (light green, yellow), packed in a serial storage box

Commercial data

EAN	 4 046356 452526
Pack	1 pcs.
Customs tariff	82032000
Catalog page information	Page 280 (CL2-2011)

Product notes

WEEE/RoHS-compliant since:
09/26/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Length (b)	114 mm
Height	25.5 mm
Width (a)	75 mm
Color	black
Weight	66 g

Die station	Crimping position 1
Min. cross section	0.1 mm ²
Max. cross section	0.4 mm ²
AWG min	26
AWG max	22
Die station	Crimping position 2
Min. cross section	4 mm ²
Max. cross section	6 mm ²
AWG min	12
AWG max	10
Compression	Oval crimp
Type of contact	Insulated cable lugs

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2012 Phoenix Contact
Technical modifications reserved;