



1918691-8 Product Details

[Share](#) [Print](#) [Email](#)

1918691-8

TE Internal Number: 1918691-8

Active

Fiber Optic Cable Assemblies

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Patch Cord
- Cable Assembly
- LC Fiber Optic Cable Connector Type, MT-RJ SECURE (No Pins) Fiber Optic Cable Connector Type
- Fiber Type = OM1 62.5/125 Micron
- Cable Assembly Type = MT-RJ SECURE (No Pins) to LC Duplex

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

| Documentation & Additional Information | |
|--|--|
| Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later. | Related Products: <ul style="list-style-type: none"> • Tooling |

| Product Features (Please use the Product Drawing for all design activity) | |
|---|---|
| <p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Designation = Patch Cord • Product Type = Cable Assembly • Fiber Optic Cable Connector Type = LC, MT-RJ SECURE (No Pins) • Cable Assembly Type = MT-RJ SECURE (No Pins) to LC Duplex • Cable Type = Twin Zip <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Insertion Loss (dB) = 0.50 • Return Loss (dB) = 20 <p>Termination Features:</p> <ul style="list-style-type: none"> • Fiber Type (Micron) = OM1 62.5/125 <p>Dimensions:</p> <ul style="list-style-type: none"> • Cable Diameter (mm [in]) = 1.80 [.071] • Length (M [ft]) = 8.00 [26.25] <p>Body Features:</p> <ul style="list-style-type: none"> • Cable Color = Orange • Connector Color = Violet • Boot Body Style - Left = Standard • Boot Color - Left = Beige • Boot Body Style - Right = Standard • Boot Color - Right = Beige/Beige • Ferrule Material = Ceramic | <p>Contact Features:</p> <ul style="list-style-type: none"> • Fibre Channel = No <p>Housing Features:</p> <ul style="list-style-type: none"> • Fiber Path Configuration = Pair Flipped <p>Configuration Features:</p> <ul style="list-style-type: none"> • Mode = Multimode • Number of Fibers = 2 • Cable Buffering = Tight Buffered • Connector(s) Exit Angle to Connector(s) Exit Angle = 180° to 180° <p>Industry Standards:</p> <ul style="list-style-type: none"> • Flammability Rating Type = OFNR (Riser) Jacket • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Product Availability:</p> <ul style="list-style-type: none"> • Region = Asia, North America, Latin America <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity |

Feedback

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



