

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

[. My Account](#)


- [Sign In](#)
- [Register](#)

[. Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors](#) > [Product Feature Selector](#) > Product Details

1375583-5 Product Details



1375583-5



[Active](#)

.100 AMPMODU Headers, Housings & Contacts

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

Product Highlights:

- Header
- Number of Positions = 6
- Number of Rows = Single
- Post Size = 0.64 [.025] mm [in]
- Terminate To Printed Circuit Board

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [AMPMODU MTE SURFACE MOUNT, VERTICAL HEADER ASSEMBLY](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version D)
- [3D Model](#) (IGES, Version D)
- [3D Model](#) (STEP, Version D)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- [Product Type](#) = Header
- [Number of Positions](#) = 6
- [Post Size \(mm \[in\]\)](#) = 0.64 [.025]
- [PCB Mount Angle](#) = Vertical
- [PCB Retention Feature](#) = Yes
- [PCB Mount Style](#) = Surface Mount
- [Mating Polarization](#) = With
- [Mating Polarization Method](#) = Latched
- [Connector Series](#) = MTE
- Wire Termination Type = Crimp, Insulation Displacement Crimp (IDC)
- Comment = Use Keying Tool No. 91417-1 to remove post for keying.

Electrical Characteristics:

- Contact Current Rating (Amps.) = 3
- Termination Resistance (m Ω) = 15
- Insulation Resistance (M Ω) = 5,000
- Dielectric Withstanding Voltage (V) = 600

Termination Related Features:

- Solder Tail Contact Plating = Tin-Lead

Body Related Features:

- [Number of Rows](#) = Single
- [Centerline, Matrix \(mm \[in\]\)](#) = 2.54 [.100]

Contact Related Features:

- [PCB Orientation Feature](#) = No
- [Contact Mating Area Plating Material](#) = Gold (30)
- Contact Material = Brass
- Approved Standards = UL E28476, CSA LR7189

Housing Related Features:

- [Housing Color](#) = Black
- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C

Conditions for Usage:

- [Terminate To](#) = Printed Circuit Board
- Temperature Rating = High
- Operating Temperature (°C) = -65 – +105

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved